


FormPopup

 Apr 28, 2024 17:26

Supported Clients

NGClient

Methods Summary

Object	component()	Get the component form popup will be shown relative to.
void	component(component)	Set component form popup will be shown relative to.
String	datapreviewer()	Get the popup form datapreviewer (which was set using setter).
void	datapreviewer(datapreviewer)	Set form popup datapreviewer that will be set.
Number	height()	Get the popup form height (which was set using setter).
void	height(height)	Set form popup height.
Object	scope()	Get the popup form scope (which was set using setter).
void	scope(scope)	Set form popup scope that will be modified.
void	show()	Show form popup using parameters that were set
Boolean	showBackdrop()	Get the popup form show backdrop (which was set using setter).
void	showBackdrop(showBackdrop)	Set whether backdrop will be shown.
Number	width()	Get the popup form width (which was set using setter).
void	width(width)	Set form popup width.
Number	x()	Get the popup form x location (which was set using setter).
void	x(x)	Set form popup x location.
Number	y()	Get the popup form y location (which was set using setter).
void	y(y)	Set form popup y location.

Methods Details

component()
Get the component form popup will be shown relative to.

Returns
[Object](#) IComponent

Supported Clients
NGClient

Sample

```
popupform.component();
```

component(component)
Set component form popup will be shown relative to. If null, will use coordinates or show at screen center.

Parameters
[Object](#) component the form to show

Supported Clients
NGClient

Sample

```
plugins.window.createFormPopup(forms.orderPicker).component(elements.myelement).show();
```

datapreviewer()
Get the popup form datapreviewer (which was set using setter).

Returns
[String](#) String

Supported Clients
NGClient

Sample

```
popupform.dataprovider();
```

dataprovider(dataprovider)

Set form popup dataprovider that will be set. If this is set, also scope needs to be specified.

Parameters

[String](#) dataprovider form popup dataprovider

Supported Clients

NGClient

Sample

```
plugins.window.createFormPopup(forms.orderPicker).dataprovider('myid').scope(foundset.getSelectedRecord()).show();
```

height()

Get the popup form height (which was set using setter).

Returns

[Number](#) int

Supported Clients

NGClient

Sample

```
popupform.height();
```

height(height)

Set form popup height. If not set, form design height will be used.

Parameters

[Number](#) height form popup height

Supported Clients

NGClient

Sample

```
plugins.window.createFormPopup(forms.orderPicker).height(100).show();
```

scope()

Get the popup form scope (which was set using setter).

Returns

[Object](#) Object

Supported Clients

NGClient

Sample

```
popupform.scope();
```

scope(scope)

Set form popup scope that will be modified. If this is set, also dataprovider needs to be specified.

Parameters

[Object](#) scope form popup scope to modify

Supported Clients

NGClient

Sample

```
plugins.window.createFormPopup(forms.orderPicker).dataprovder('myid').scope(foundset.getSelectedRecord()).show();
```

show()

Show form popup using parameters that were set

Supported Clients

NGClient

Sample

```
plugins.window.createFormPopup(forms.orderPicker).x(100).y(100).width(100).height(100).showBackdrop(true).show();
```

showBackdrop()

Get the popup form show backdrop (which was set using setter).

Returns

[Boolean](#) boolean

Supported Clients

NGClient

Sample

```
popupform.showBackdrop();
```

showBackdrop(showBackdrop)

Set whether backdrop will be shown. Default value is false.

Parameters

[Boolean](#) showBackdrop form popup showBackdrop

Supported Clients

NGClient

Sample

```
plugins.window.createFormPopup(forms.orderPicker).showBackdrop(true).show();
```

width()

Get the popup form width (which was set using setter).

Returns

[Number](#) int

Supported Clients

NGClient

Sample

```
popupform.width();
```

width(width)

Set form popup width. If not set, form design width will be used.

Parameters

[Number](#) width form popup width

Supported Clients

NGClient

Sample

```
plugins.window.createFormPopup(forms.orderPicker).width(100).show();
```

x()

Get the popup form x location (which was set using setter).

Returns

[Number](#) int

Supported Clients

NGClient

Sample

```
popupform.x();
```

x(x)

Set form popup x location. The priority sequence for location is: related element, set location, center of screen.

Parameters

[Number](#) x form popup x location

Supported Clients

NGClient

Sample

```
plugins.window.createFormPopup(forms.orderPicker).x(100).show();
```

y()

Get the popup form y location (which was set using setter).

Returns

[Number](#) int

Supported Clients

NGClient

Sample

```
popupform.y();
```

y(y)

Set form popup y location. The priority sequence for location is: related element, set location, center of screen.

Parameters

[Number](#) y form popup y location

Supported Clients

NGClient

Sample

```
plugins.window.createFormPopup(forms.orderPicker).y(100).show();
```