ServoyException

Feb 26, 2024 08:56

Supported Clients

SmartClient WebClient NGClient

Constants Summary

Number	ABSTRACT_FORM	Exception code for ABSTRACT_FORM.
Number	ACQUIRE_LOCK_FAILURE	Exception code for ACQUIRE_LOCK_FAILURE.
Number	BAD_SQL_SYNTAX	Exception code for BAD_SQL_SYNTAX.
Number	CLIENT_NOT_AUTHORIZED	Exception code for CLIENT_NOT_AUTHORIZED.
Number	DATA_ACCESS_RESOURCE_FAILURE	Exception code for DATA_ACCESS_RESOURCE_FAILURE.
Number	DATA_INTEGRITY_VIOLATION	Exception code for DATA_INTEGRITY_VIOLATION.
Number	DEADLOCK	Exception code for DEADLOCK.
Number	DELETE_NOT_GRANTED	Exception code for DELETE_NOT_GRANTED.
Number	EXECUTE_PROGRAM_FAILED	Exception code for EXECUTE_PROGRAM_FAILED.
Number	INCORRECT_LOGIN	Exception code for INCORRECT_LOGIN.
Number	INVALID_INPUT	Exception code for INVALID_INPUT.
Number	INVALID_RESULTSET_ACCESS	Exception code for INVALID_RESULTSET_ACCESS.
Number	MAINTENANCE_MODE	Exception code for MAINTENANCE_MODE.
Number	NO_ACCESS	Exception code for NO_ACCESS.
Number	NO_CREATE_ACCESS	Exception code for NO_CREATE_ACCESS.
Number	NO_DELETE_ACCESS	Exception code for NO_DELETE_ACCESS.
Number	NO_LICENSE	Exception code for NO_LICENSE.
Number	NO_MODIFY_ACCESS	Exception code for NO_MODIFY_ACCESS.
Number	NO_PARENT_DELETE_WITH_RELATED_RECORDS	Exception code for NO_PARENT_DELETE_WITH_RELATED_RECORDS.
Number	NO_RELATED_CREATE_ACCESS	Exception code for NO_RELATED_CREATE_ACCESS.
Number	PERMISSION_DENIED	Exception code for PERMISSION_DENIED.
Number	RECORD_LOCKED	Exception code for RECORD_LOCKED.
Number	RECORD_VALIDATION_FAILED	Exception code for RECORD_VALIDATION_FAILED.
Number	SAVE_FAILED	Exception code for SAVE_FAILED.
Number	UNEXPECTED_UPDATE_COUNT	Exception code for UNEXPECTED_UPDATE_COUNT.
Number	UNKNOWN_DATABASE_EXCEPTION	Exception code for UNKNOWN_DATABASE_EXCEPTION.

Methods Summary

String	getContext()	
Number	getErrorCode()	Returns the error code for this ServoyException.
String	getMessage()	Returns the string message for this ServoyException.
String	getScriptStackTrace()	Returns the script stack trace for this ServoyException if this could be created.
String	getStackTrace()	Returns the stack trace for this ServoyException.

Constants Details

ABSTRACT_FORM

```
Exception code for ABSTRACT_FORM.

This code is used when a form, that cannot be created, is shown (for example, a form without parts).
```

Returns

Number

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//this sample script should be attached to onError method handler in the solution settings
application.output('Exception Object: '+ex)
application.output('MSG: '+ex.getMessage())
if (ex instanceof ServoyException)
{
	/** @type {ServoyException} */
	var servoyException = ex;
	application.output("is a ServoyException")
	application.output("Errorcode: "+servoyException.getErrorCode())
	var trace = "";
	if (ex.getScriptStackTrace) trace = servoyException.getScriptStackTrace();
	else if (servoyException.getStackTrace)  trace = servoyException.getStackTrace();
	if (servoyException.getErrorCode() == ServoyException.SAVE_FAILED)
	{
		plugins.dialogs.showErrorDialog( 'Error',  'It seems you did not fill in a required field',
'OK');
		//Get the failed records after a save
		var array = databaseManager.getFailedRecords()
		for( var i = 0 ; i < array.length ; i++ )
		{
			var record = array[i];
			application.output(record.exception);
			if (record.exception instanceof DataException)
			{
				/** @type {DataException} */
				var dataException = record.exception;
				application.output('SQL: '+dataException.getSQL())
				application.output('SQLState: '+dataException.getSQLState())
				application.output('VendorErrorCode: '+dataException.getVendorErrorCode())
			}
		}
		return false
	}
}
//if returns false or no return, error is not reported to client; if returns true error is reported
//by default error report means logging the error, in smart client an error dialog will also show up
return true
```

ACQUIRE_LOCK_FAILURE

Exception code for ACQUIRE_LOCK_FAILURE.

This code is used when a database failed to lock a row or table.

Returns

Number

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//this sample script should be attached to onError method handler in the solution settings
application.output('Exception Object: '+ex)
application.output('MSG: '+ex.getMessage())
if (ex instanceof ServoyException)
{
	/** @type {ServoyException} */
	var servoyException = ex;
	application.output("is a ServoyException")
	application.output("Errorcode: "+servoyException.getErrorCode())
	var trace = "";
	if (ex.getScriptStackTrace) trace = servoyException.getScriptStackTrace();
	else if (servoyException.getStackTrace)  trace = servoyException.getStackTrace();
	if (servoyException.getErrorCode() == ServoyException.SAVE_FAILED)
	{
		plugins.dialogs.showErrorDialog( 'Error',  'It seems you did not fill in a required field',
'OK');
		//Get the failed records after a save
		var array = databaseManager.getFailedRecords()
		for( var i = 0 ; i < array.length ; i++ )
		{
			var record = array[i];
			application.output(record.exception);
			if (record.exception instanceof DataException)
			{
				/** @type {DataException} */
				var dataException = record.exception;
				application.output('SQL: '+dataException.getSQL())
				application.output('SQLState: '+dataException.getSQLState())
				application.output('VendorErrorCode: '+dataException.getVendorErrorCode())
			}
		}
		return false
	}
}
//if returns false or no return, error is not reported to client; if returns true error is reported
//by default error report means logging the error, in smart client an error dialog will also show up
return true
```

BAD_SQL_SYNTAX

Exception code for BAD_SQL_SYNTAX.

This code is used when a database exception is recognized as an sql syntax error.

Returns

Number

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//this sample script should be attached to onError method handler in the solution settings
application.output('Exception Object: '+ex)
application.output('MSG: '+ex.getMessage())
if (ex instanceof ServoyException)
{
	/** @type {ServoyException} */
	var servoyException = ex;
	application.output("is a ServoyException")
	application.output("Errorcode: "+servoyException.getErrorCode())
	var trace = "";
	if (ex.getScriptStackTrace) trace = servoyException.getScriptStackTrace();
	else if (servoyException.getStackTrace)  trace = servoyException.getStackTrace();
	if (servoyException.getErrorCode() == ServoyException.SAVE_FAILED)
	{
		plugins.dialogs.showErrorDialog( 'Error',  'It seems you did not fill in a required field',
'OK');
		//Get the failed records after a save
		var array = databaseManager.getFailedRecords()
		for( var i = 0 ; i < array.length ; i++ )
		{
			var record = array[i];
			application.output(record.exception);
			if (record.exception instanceof DataException)
			{
				/** @type {DataException} */
				var dataException = record.exception;
				application.output('SQL: '+dataException.getSQL())
				application.output('SQLState: '+dataException.getSQLState())
				application.output('VendorErrorCode: '+dataException.getVendorErrorCode())
			}
		}
		return false
	}
}
//if returns false or no return, error is not reported to client; if returns true error is reported
//by default error report means logging the error, in smart client an error dialog will also show up
return true
```

CLIENT_NOT_AUTHORIZED

Exception code for CLIENT_NOT_AUTHORIZED.

This code is used when an client performs an action that requires the user to be logged in and the user has not logged in yet.

Returns

Number

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//this sample script should be attached to onError method handler in the solution settings
application.output('Exception Object: '+ex)
application.output('MSG: '+ex.getMessage())
if (ex instanceof ServoyException)
{
	/** @type {ServoyException} */
	var servoyException = ex;
	application.output("is a ServoyException")
	application.output("Errorcode: "+servoyException.getErrorCode())
	var trace = "";
	if (ex.getScriptStackTrace) trace = servoyException.getScriptStackTrace();
	else if (servoyException.getStackTrace)  trace = servoyException.getStackTrace();
	if (servoyException.getErrorCode() == ServoyException.SAVE_FAILED)
	{
		plugins.dialogs.showErrorDialog( 'Error',  'It seems you did not fill in a required field',
'OK');
		//Get the failed records after a save
		var array = databaseManager.getFailedRecords()
		for( var i = 0 ; i < array.length ; i++ )
		{
			var record = array[i];
			application.output(record.exception);
			if (record.exception instanceof DataException)
			{
				/** @type {DataException} */
				var dataException = record.exception;
				application.output('SQL: '+dataException.getSQL())
				application.output('SQLState: '+dataException.getSQLState())
				application.output('VendorErrorCode: '+dataException.getVendorErrorCode())
			}
		}
		return false
	}
}
//if returns false or no return, error is not reported to client; if returns true error is reported
//by default error report means logging the error, in smart client an error dialog will also show up
return true
```

DATA_ACCESS_RESOURCE_FAILURE

Exception code for DATA_ACCESS_RESOURCE_FAILURE.

This code is used when a database exception received an error accessing storage devices.

Returns

Number

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//this sample script should be attached to onError method handler in the solution settings
application.output('Exception Object: '+ex)
application.output('MSG: '+ex.getMessage())
if (ex instanceof ServoyException)
{
	/** @type {ServoyException} */
	var servoyException = ex;
	application.output("is a ServoyException")
	application.output("Errorcode: "+servoyException.getErrorCode())
	var trace = "";
	if (ex.getScriptStackTrace) trace = servoyException.getScriptStackTrace();
	else if (servoyException.getStackTrace)  trace = servoyException.getStackTrace();
	if (servoyException.getErrorCode() == ServoyException.SAVE_FAILED)
	{
		plugins.dialogs.showErrorDialog( 'Error',  'It seems you did not fill in a required field',
'OK');
		//Get the failed records after a save
		var array = databaseManager.getFailedRecords()
		for( var i = 0 ; i < array.length ; i++ )
		{
			var record = array[i];
			application.output(record.exception);
			if (record.exception instanceof DataException)
			{
				/** @type {DataException} */
				var dataException = record.exception;
				application.output('SQL: '+dataException.getSQL())
				application.output('SQLState: '+dataException.getSQLState())
				application.output('VendorErrorCode: '+dataException.getVendorErrorCode())
			}
		}
		return false
	}
}
//if returns false or no return, error is not reported to client; if returns true error is reported
//by default error report means logging the error, in smart client an error dialog will also show up
return true
```

DATA_INTEGRITY_VIOLATION

Exception code for DATA_INTEGRITY_VIOLATION.

This code is used when a database exception is recognized as an integrity exception (like constraint violation).

Returns

Number

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//this sample script should be attached to onError method handler in the solution settings
application.output('Exception Object: '+ex)
application.output('MSG: '+ex.getMessage())
if (ex instanceof ServoyException)
{
	/** @type {ServoyException} */
	var servoyException = ex;
	application.output("is a ServoyException")
	application.output("Errorcode: "+servoyException.getErrorCode())
	var trace = "";
	if (ex.getScriptStackTrace) trace = servoyException.getScriptStackTrace();
	else if (servoyException.getStackTrace)  trace = servoyException.getStackTrace();
	if (servoyException.getErrorCode() == ServoyException.SAVE_FAILED)
	{
		plugins.dialogs.showErrorDialog( 'Error',  'It seems you did not fill in a required field',
'OK');
		//Get the failed records after a save
		var array = databaseManager.getFailedRecords()
		for( var i = 0 ; i < array.length ; i++ )
		{
			var record = array[i];
			application.output(record.exception);
			if (record.exception instanceof DataException)
			{
				/** @type {DataException} */
				var dataException = record.exception;
				application.output('SQL: '+dataException.getSQL())
				application.output('SQLState: '+dataException.getSQLState())
				application.output('VendorErrorCode: '+dataException.getVendorErrorCode())
			}
		}
		return false
	}
}
//if returns false or no return, error is not reported to client; if returns true error is reported
//by default error report means logging the error, in smart client an error dialog will also show up
return true
```

DEADLOCK

Exception code for DEADLOCK.

This code is used when a deadlock is detected by the database.

Returns

Number

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//this sample script should be attached to onError method handler in the solution settings
application.output('Exception Object: '+ex)
application.output('MSG: '+ex.getMessage())
if (ex instanceof ServoyException)
{
	/** @type {ServoyException} */
	var servoyException = ex;
	application.output("is a ServoyException")
	application.output("Errorcode: "+servoyException.getErrorCode())
	var trace = "";
	if (ex.getScriptStackTrace) trace = servoyException.getScriptStackTrace();
	else if (servoyException.getStackTrace)  trace = servoyException.getStackTrace();
	if (servoyException.getErrorCode() == ServoyException.SAVE_FAILED)
	{
		plugins.dialogs.showErrorDialog( 'Error',  'It seems you did not fill in a required field',
'OK');
		//Get the failed records after a save
		var array = databaseManager.getFailedRecords()
		for( var i = 0 ; i < array.length ; i++ )
		{
			var record = array[i];
			application.output(record.exception);
			if (record.exception instanceof DataException)
			{
				/** @type {DataException} */
				var dataException = record.exception;
				application.output('SQL: '+dataException.getSQL())
				application.output('SQLState: '+dataException.getSQLState())
				application.output('VendorErrorCode: '+dataException.getVendorErrorCode())
			}
		}
		return false
	}
}
//if returns false or no return, error is not reported to client; if returns true error is reported
//by default error report means logging the error, in smart client an error dialog will also show up
return true
```

DELETE_NOT_GRANTED

Exception code for DELETE_NOT_GRANTED.

This code is used when a record deletion was rejected by a pre-delete Servoy trigger.

Returns

Number

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//this sample script should be attached to onError method handler in the solution settings
application.output('Exception Object: '+ex)
application.output('MSG: '+ex.getMessage())
if (ex instanceof ServoyException)
{
	/** @type {ServoyException} */
	var servoyException = ex;
	application.output("is a ServoyException")
	application.output("Errorcode: "+servoyException.getErrorCode())
	var trace = "";
	if (ex.getScriptStackTrace) trace = servoyException.getScriptStackTrace();
	else if (servoyException.getStackTrace)  trace = servoyException.getStackTrace();
	if (servoyException.getErrorCode() == ServoyException.SAVE_FAILED)
	{
		plugins.dialogs.showErrorDialog( 'Error',  'It seems you did not fill in a required field',
'OK');
		//Get the failed records after a save
		var array = databaseManager.getFailedRecords()
		for( var i = 0 ; i < array.length ; i++ )
		{
			var record = array[i];
			application.output(record.exception);
			if (record.exception instanceof DataException)
			{
				/** @type {DataException} */
				var dataException = record.exception;
				application.output('SQL: '+dataException.getSQL())
				application.output('SQLState: '+dataException.getSQLState())
				application.output('VendorErrorCode: '+dataException.getVendorErrorCode())
			}
		}
		return false
	}
}
//if returns false or no return, error is not reported to client; if returns true error is reported
//by default error report means logging the error, in smart client an error dialog will also show up
return true
```

EXECUTE_PROGRAM_FAILED

Exception code for EXECUTE_PROGRAM_FAILED.

This code is used when an external program was not executed correctly.

Returns

Number

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//this sample script should be attached to onError method handler in the solution settings
application.output('Exception Object: '+ex)
application.output('MSG: '+ex.getMessage())
if (ex instanceof ServoyException)
{
	/** @type {ServoyException} */
	var servoyException = ex;
	application.output("is a ServoyException")
	application.output("Errorcode: "+servoyException.getErrorCode())
	var trace = "";
	if (ex.getScriptStackTrace) trace = servoyException.getScriptStackTrace();
	else if (servoyException.getStackTrace)  trace = servoyException.getStackTrace();
	if (servoyException.getErrorCode() == ServoyException.SAVE_FAILED)
	{
		plugins.dialogs.showErrorDialog( 'Error',  'It seems you did not fill in a required field',
'OK');
		//Get the failed records after a save
		var array = databaseManager.getFailedRecords()
		for( var i = 0 ; i < array.length ; i++ )
		{
			var record = array[i];
			application.output(record.exception);
			if (record.exception instanceof DataException)
			{
				/** @type {DataException} */
				var dataException = record.exception;
				application.output('SQL: '+dataException.getSQL())
				application.output('SQLState: '+dataException.getSQLState())
				application.output('VendorErrorCode: '+dataException.getVendorErrorCode())
			}
		}
		return false
	}
}
//if returns false or no return, error is not reported to client; if returns true error is reported
//by default error report means logging the error, in smart client an error dialog will also show up
return true
```

INCORRECT_LOGIN

Exception code for INCORRECT_LOGIN.

This code is used when the user enters invalid credentials.

Returns

Number

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//this sample script should be attached to onError method handler in the solution settings
application.output('Exception Object: '+ex)
application.output('MSG: '+ex.getMessage())
if (ex instanceof ServoyException)
{
	/** @type {ServoyException} */
	var servoyException = ex;
	application.output("is a ServoyException")
	application.output("Errorcode: "+servoyException.getErrorCode())
	var trace = "";
	if (ex.getScriptStackTrace) trace = servoyException.getScriptStackTrace();
	else if (servoyException.getStackTrace)  trace = servoyException.getStackTrace();
	if (servoyException.getErrorCode() == ServoyException.SAVE_FAILED)
	{
		plugins.dialogs.showErrorDialog( 'Error',  'It seems you did not fill in a required field',
'OK');
		//Get the failed records after a save
		var array = databaseManager.getFailedRecords()
		for( var i = 0 ; i < array.length ; i++ )
		{
			var record = array[i];
			application.output(record.exception);
			if (record.exception instanceof DataException)
			{
				/** @type {DataException} */
				var dataException = record.exception;
				application.output('SQL: '+dataException.getSQL())
				application.output('SQLState: '+dataException.getSQLState())
				application.output('VendorErrorCode: '+dataException.getVendorErrorCode())
			}
		}
		return false
	}
}
//if returns false or no return, error is not reported to client; if returns true error is reported
//by default error report means logging the error, in smart client an error dialog will also show up
return true
```

INVALID_INPUT

Exception code for INVALID_INPUT.

This code is used when the user enters data that could not be validated.

Returns

Number

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//this sample script should be attached to onError method handler in the solution settings
application.output('Exception Object: '+ex)
application.output('MSG: '+ex.getMessage())
if (ex instanceof ServoyException)
{
	/** @type {ServoyException} */
	var servoyException = ex;
	application.output("is a ServoyException")
	application.output("Errorcode: "+servoyException.getErrorCode())
	var trace = "";
	if (ex.getScriptStackTrace) trace = servoyException.getScriptStackTrace();
	else if (servoyException.getStackTrace)  trace = servoyException.getStackTrace();
	if (servoyException.getErrorCode() == ServoyException.SAVE_FAILED)
	{
		plugins.dialogs.showErrorDialog( 'Error',  'It seems you did not fill in a required field',
'OK');
		//Get the failed records after a save
		var array = databaseManager.getFailedRecords()
		for( var i = 0 ; i < array.length ; i++ )
		{
			var record = array[i];
			application.output(record.exception);
			if (record.exception instanceof DataException)
			{
				/** @type {DataException} */
				var dataException = record.exception;
				application.output('SQL: '+dataException.getSQL())
				application.output('SQLState: '+dataException.getSQLState())
				application.output('VendorErrorCode: '+dataException.getVendorErrorCode())
			}
		}
		return false
	}
}
//if returns false or no return, error is not reported to client; if returns true error is reported
//by default error report means logging the error, in smart client an error dialog will also show up
return true
```

INVALID_RESULTSET_ACCESS

Exception code for INVALID_RESULTSET_ACCESS.

This code is used when a data is requested that is not selected in the sql.

Returns

Number

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//this sample script should be attached to onError method handler in the solution settings
application.output('Exception Object: '+ex)
application.output('MSG: '+ex.getMessage())
if (ex instanceof ServoyException)
{
	/** @type {ServoyException} */
	var servoyException = ex;
	application.output("is a ServoyException")
	application.output("Errorcode: "+servoyException.getErrorCode())
	var trace = "";
	if (ex.getScriptStackTrace) trace = servoyException.getScriptStackTrace();
	else if (servoyException.getStackTrace)  trace = servoyException.getStackTrace();
	if (servoyException.getErrorCode() == ServoyException.SAVE_FAILED)
	{
		plugins.dialogs.showErrorDialog( 'Error',  'It seems you did not fill in a required field',
'OK');
		//Get the failed records after a save
		var array = databaseManager.getFailedRecords()
		for( var i = 0 ; i < array.length ; i++ )
		{
			var record = array[i];
			application.output(record.exception);
			if (record.exception instanceof DataException)
			{
				/** @type {DataException} */
				var dataException = record.exception;
				application.output('SQL: '+dataException.getSQL())
				application.output('SQLState: '+dataException.getSQLState())
				application.output('VendorErrorCode: '+dataException.getVendorErrorCode())
			}
		}
		return false
	}
}
//if returns false or no return, error is not reported to client; if returns true error is reported
//by default error report means logging the error, in smart client an error dialog will also show up
return true
```

MAINTENANCE_MODE

Exception code for MAINTENANCE_MODE.

This code is used when a client could not be registered with the server because the server is in maintenance mode.

Returns

Number

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//this sample script should be attached to onError method handler in the solution settings
application.output('Exception Object: '+ex)
application.output('MSG: '+ex.getMessage())
if (ex instanceof ServoyException)
{
	/** @type {ServoyException} */
	var servoyException = ex;
	application.output("is a ServoyException")
	application.output("Errorcode: "+servoyException.getErrorCode())
	var trace = "";
	if (ex.getScriptStackTrace) trace = servoyException.getScriptStackTrace();
	else if (servoyException.getStackTrace)  trace = servoyException.getStackTrace();
	if (servoyException.getErrorCode() == ServoyException.SAVE_FAILED)
	{
		plugins.dialogs.showErrorDialog( 'Error',  'It seems you did not fill in a required field',
'OK');
		//Get the failed records after a save
		var array = databaseManager.getFailedRecords()
		for( var i = 0 ; i < array.length ; i++ )
		{
			var record = array[i];
			application.output(record.exception);
			if (record.exception instanceof DataException)
			{
				/** @type {DataException} */
				var dataException = record.exception;
				application.output('SQL: '+dataException.getSQL())
				application.output('SQLState: '+dataException.getSQLState())
				application.output('VendorErrorCode: '+dataException.getVendorErrorCode())
			}
		}
		return false
	}
}
//if returns false or no return, error is not reported to client; if returns true error is reported
//by default error report means logging the error, in smart client an error dialog will also show up
return true
```

NO_ACCESS

Exception code for NO_ACCESS.

This code is used when a user wants to view data and this is disallowed by security settings.

Returns

Number

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//this sample script should be attached to onError method handler in the solution settings
application.output('Exception Object: '+ex)
application.output('MSG: '+ex.getMessage())
if (ex instanceof ServoyException)
{
	/** @type {ServoyException} */
	var servoyException = ex;
	application.output("is a ServoyException")
	application.output("Errorcode: "+servoyException.getErrorCode())
	var trace = "";
	if (ex.getScriptStackTrace) trace = servoyException.getScriptStackTrace();
	else if (servoyException.getStackTrace)  trace = servoyException.getStackTrace();
	if (servoyException.getErrorCode() == ServoyException.SAVE_FAILED)
	{
		plugins.dialogs.showErrorDialog( 'Error',  'It seems you did not fill in a required field',
'OK');
		//Get the failed records after a save
		var array = databaseManager.getFailedRecords()
		for( var i = 0 ; i < array.length ; i++ )
		{
			var record = array[i];
			application.output(record.exception);
			if (record.exception instanceof DataException)
			{
				/** @type {DataException} */
				var dataException = record.exception;
				application.output('SQL: '+dataException.getSQL())
				application.output('SQLState: '+dataException.getSQLState())
				application.output('VendorErrorCode: '+dataException.getVendorErrorCode())
			}
		}
		return false
	}
}
//if returns false or no return, error is not reported to client; if returns true error is reported
//by default error report means logging the error, in smart client an error dialog will also show up
return true
```

NO_CREATE_ACCESS

Exception code for NO_CREATE_ACCESS.

This code is used when a user wants to create new records and this is disallowed by security settings.

Returns

Number

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//this sample script should be attached to onError method handler in the solution settings
application.output('Exception Object: '+ex)
application.output('MSG: '+ex.getMessage())
if (ex instanceof ServoyException)
{
	/** @type {ServoyException} */
	var servoyException = ex;
	application.output("is a ServoyException")
	application.output("Errorcode: "+servoyException.getErrorCode())
	var trace = "";
	if (ex.getScriptStackTrace) trace = servoyException.getScriptStackTrace();
	else if (servoyException.getStackTrace)  trace = servoyException.getStackTrace();
	if (servoyException.getErrorCode() == ServoyException.SAVE_FAILED)
	{
		plugins.dialogs.showErrorDialog( 'Error',  'It seems you did not fill in a required field',
'OK');
		//Get the failed records after a save
		var array = databaseManager.getFailedRecords()
		for( var i = 0 ; i < array.length ; i++ )
		{
			var record = array[i];
			application.output(record.exception);
			if (record.exception instanceof DataException)
			{
				/** @type {DataException} */
				var dataException = record.exception;
				application.output('SQL: '+dataException.getSQL())
				application.output('SQLState: '+dataException.getSQLState())
				application.output('VendorErrorCode: '+dataException.getVendorErrorCode())
			}
		}
		return false
	}
}
//if returns false or no return, error is not reported to client; if returns true error is reported
//by default error report means logging the error, in smart client an error dialog will also show up
return true
```

NO_DELETE_ACCESS

Exception code for NO_DELETE_ACCESS.

This code is used when a user wants to delete data and this is disallowed by security settings.

Returns

Number

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//this sample script should be attached to onError method handler in the solution settings
application.output('Exception Object: '+ex)
application.output('MSG: '+ex.getMessage())
if (ex instanceof ServoyException)
{
	/** @type {ServoyException} */
	var servoyException = ex;
	application.output("is a ServoyException")
	application.output("Errorcode: "+servoyException.getErrorCode())
	var trace = "";
	if (ex.getScriptStackTrace) trace = servoyException.getScriptStackTrace();
	else if (servoyException.getStackTrace)  trace = servoyException.getStackTrace();
	if (servoyException.getErrorCode() == ServoyException.SAVE_FAILED)
	{
		plugins.dialogs.showErrorDialog( 'Error',  'It seems you did not fill in a required field',
'OK');
		//Get the failed records after a save
		var array = databaseManager.getFailedRecords()
		for( var i = 0 ; i < array.length ; i++ )
		{
			var record = array[i];
			application.output(record.exception);
			if (record.exception instanceof DataException)
			{
				/** @type {DataException} */
				var dataException = record.exception;
				application.output('SQL: '+dataException.getSQL())
				application.output('SQLState: '+dataException.getSQLState())
				application.output('VendorErrorCode: '+dataException.getVendorErrorCode())
			}
		}
		return false
	}
}
//if returns false or no return, error is not reported to client; if returns true error is reported
//by default error report means logging the error, in smart client an error dialog will also show up
return true
```

NO_LICENSE

Exception code for NO_LICENSE.

This code is used when a client could not be registered with the server because of license limitations.

Returns

Number

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//this sample script should be attached to onError method handler in the solution settings
application.output('Exception Object: '+ex)
application.output('MSG: '+ex.getMessage())
if (ex instanceof ServoyException)
{
	/** @type {ServoyException} */
	var servoyException = ex;
	application.output("is a ServoyException")
	application.output("Errorcode: "+servoyException.getErrorCode())
	var trace = "";
	if (ex.getScriptStackTrace) trace = servoyException.getScriptStackTrace();
	else if (servoyException.getStackTrace)  trace = servoyException.getStackTrace();
	if (servoyException.getErrorCode() == ServoyException.SAVE_FAILED)
	{
		plugins.dialogs.showErrorDialog( 'Error',  'It seems you did not fill in a required field',
'OK');
		//Get the failed records after a save
		var array = databaseManager.getFailedRecords()
		for( var i = 0 ; i < array.length ; i++ )
		{
			var record = array[i];
			application.output(record.exception);
			if (record.exception instanceof DataException)
			{
				/** @type {DataException} */
				var dataException = record.exception;
				application.output('SQL: '+dataException.getSQL())
				application.output('SQLState: '+dataException.getSQLState())
				application.output('VendorErrorCode: '+dataException.getVendorErrorCode())
			}
		}
		return false
	}
}
//if returns false or no return, error is not reported to client; if returns true error is reported
//by default error report means logging the error, in smart client an error dialog will also show up
return true
```

NO_MODIFY_ACCESS

Exception code for NO_MODIFY_ACCESS.

This code is used when a user wants to update data and this is disallowed by security settings.

Returns

Number

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//this sample script should be attached to onError method handler in the solution settings
application.output('Exception Object: '+ex)
application.output('MSG: '+ex.getMessage())
if (ex instanceof ServoyException)
{
	/** @type {ServoyException} */
	var servoyException = ex;
	application.output("is a ServoyException")
	application.output("Errorcode: "+servoyException.getErrorCode())
	var trace = "";
	if (ex.getScriptStackTrace) trace = servoyException.getScriptStackTrace();
	else if (servoyException.getStackTrace)  trace = servoyException.getStackTrace();
	if (servoyException.getErrorCode() == ServoyException.SAVE_FAILED)
	{
		plugins.dialogs.showErrorDialog( 'Error',  'It seems you did not fill in a required field',
'OK');
		//Get the failed records after a save
		var array = databaseManager.getFailedRecords()
		for( var i = 0 ; i < array.length ; i++ )
		{
			var record = array[i];
			application.output(record.exception);
			if (record.exception instanceof DataException)
			{
				/** @type {DataException} */
				var dataException = record.exception;
				application.output('SQL: '+dataException.getSQL())
				application.output('SQLState: '+dataException.getSQLState())
				application.output('VendorErrorCode: '+dataException.getVendorErrorCode())
			}
		}
		return false
	}
}
//if returns false or no return, error is not reported to client; if returns true error is reported
//by default error report means logging the error, in smart client an error dialog will also show up
return true
```

NO_PARENT_DELETE_WITH_RELATED_RECORDS

Exception code for NO_PARENT_DELETE_WITH_RELATED_RECORDS.

This code is used when a record could not be deleted because a non-empty relation exists for the record that does not allow parent delete when having related records.

Returns

Number

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//this sample script should be attached to onError method handler in the solution settings
application.output('Exception Object: '+ex)
application.output('MSG: '+ex.getMessage())
if (ex instanceof ServoyException)
{
	/** @type {ServoyException} */
	var servoyException = ex;
	application.output("is a ServoyException")
	application.output("Errorcode: "+servoyException.getErrorCode())
	var trace = "";
	if (ex.getScriptStackTrace) trace = servoyException.getScriptStackTrace();
	else if (servoyException.getStackTrace)  trace = servoyException.getStackTrace();
	if (servoyException.getErrorCode() == ServoyException.SAVE_FAILED)
	{
		plugins.dialogs.showErrorDialog( 'Error',  'It seems you did not fill in a required field',
'OK');
		//Get the failed records after a save
		var array = databaseManager.getFailedRecords()
		for( var i = 0 ; i < array.length ; i++ )
		{
			var record = array[i];
			application.output(record.exception);
			if (record.exception instanceof DataException)
			{
				/** @type {DataException} */
				var dataException = record.exception;
				application.output('SQL: '+dataException.getSQL())
				application.output('SQLState: '+dataException.getSQLState())
				application.output('VendorErrorCode: '+dataException.getVendorErrorCode())
			}
		}
		return false
	}
}
//if returns false or no return, error is not reported to client; if returns true error is reported
//by default error report means logging the error, in smart client an error dialog will also show up
return true
```

NO_RELATED_CREATE_ACCESS

Exception code for NO_RELATED_CREATE_ACCESS.

This code is used when a user wants to create new related records and this is disallowed by security settings.

Returns

Number

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//this sample script should be attached to onError method handler in the solution settings
application.output('Exception Object: '+ex)
application.output('MSG: '+ex.getMessage())
if (ex instanceof ServoyException)
{
	/** @type {ServoyException} */
	var servoyException = ex;
	application.output("is a ServoyException")
	application.output("Errorcode: "+servoyException.getErrorCode())
	var trace = "";
	if (ex.getScriptStackTrace) trace = servoyException.getScriptStackTrace();
	else if (servoyException.getStackTrace)  trace = servoyException.getStackTrace();
	if (servoyException.getErrorCode() == ServoyException.SAVE_FAILED)
	{
		plugins.dialogs.showErrorDialog( 'Error',  'It seems you did not fill in a required field',
'OK');
		//Get the failed records after a save
		var array = databaseManager.getFailedRecords()
		for( var i = 0 ; i < array.length ; i++ )
		{
			var record = array[i];
			application.output(record.exception);
			if (record.exception instanceof DataException)
			{
				/** @type {DataException} */
				var dataException = record.exception;
				application.output('SQL: '+dataException.getSQL())
				application.output('SQLState: '+dataException.getSQLState())
				application.output('VendorErrorCode: '+dataException.getVendorErrorCode())
			}
		}
		return false
	}
}
//if returns false or no return, error is not reported to client; if returns true error is reported
//by default error report means logging the error, in smart client an error dialog will also show up
return true
```

PERMISSION_DENIED

Exception code for PERMISSION_DENIED.

This code is used when a database exception is recognized as a authorization error.

Returns

Number

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//this sample script should be attached to onError method handler in the solution settings
application.output('Exception Object: '+ex)
application.output('MSG: '+ex.getMessage())
if (ex instanceof ServoyException)
{
	/** @type {ServoyException} */
	var servoyException = ex;
	application.output("is a ServoyException")
	application.output("Errorcode: "+servoyException.getErrorCode())
	var trace = "";
	if (ex.getScriptStackTrace) trace = servoyException.getScriptStackTrace();
	else if (servoyException.getStackTrace)  trace = servoyException.getStackTrace();
	if (servoyException.getErrorCode() == ServoyException.SAVE_FAILED)
	{
		plugins.dialogs.showErrorDialog( 'Error',  'It seems you did not fill in a required field',
'OK');
		//Get the failed records after a save
		var array = databaseManager.getFailedRecords()
		for( var i = 0 ; i < array.length ; i++ )
		{
			var record = array[i];
			application.output(record.exception);
			if (record.exception instanceof DataException)
			{
				/** @type {DataException} */
				var dataException = record.exception;
				application.output('SQL: '+dataException.getSQL())
				application.output('SQLState: '+dataException.getSQLState())
				application.output('VendorErrorCode: '+dataException.getVendorErrorCode())
			}
		}
		return false
	}
}
//if returns false or no return, error is not reported to client; if returns true error is reported
//by default error report means logging the error, in smart client an error dialog will also show up
return true
```

RECORD_LOCKED

Exception code for RECORD_LOCKED.

This code is used when a record could not be updated or deleted because it is locked by another client.

Returns

Number

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//this sample script should be attached to onError method handler in the solution settings
application.output('Exception Object: '+ex)
application.output('MSG: '+ex.getMessage())
if (ex instanceof ServoyException)
{
	/** @type {ServoyException} */
	var servoyException = ex;
	application.output("is a ServoyException")
	application.output("Errorcode: "+servoyException.getErrorCode())
	var trace = "";
	if (ex.getScriptStackTrace) trace = servoyException.getScriptStackTrace();
	else if (servoyException.getStackTrace)  trace = servoyException.getStackTrace();
	if (servoyException.getErrorCode() == ServoyException.SAVE_FAILED)
	{
		plugins.dialogs.showErrorDialog( 'Error',  'It seems you did not fill in a required field',
'OK');
		//Get the failed records after a save
		var array = databaseManager.getFailedRecords()
		for( var i = 0 ; i < array.length ; i++ )
		{
			var record = array[i];
			application.output(record.exception);
			if (record.exception instanceof DataException)
			{
				/** @type {DataException} */
				var dataException = record.exception;
				application.output('SQL: '+dataException.getSQL())
				application.output('SQLState: '+dataException.getSQLState())
				application.output('VendorErrorCode: '+dataException.getVendorErrorCode())
			}
		}
		return false
	}
}
//if returns false or no return, error is not reported to client; if returns true error is reported
//by default error report means logging the error, in smart client an error dialog will also show up
return true
```

RECORD_VALIDATION_FAILED

Exception code for RECORD_VALIDATION_FAILED.

This code is used when a record update/insert was rejected by a pre-update/insert Servoy trigger.

Returns

Number

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//this sample script should be attached to onError method handler in the solution settings
application.output('Exception Object: '+ex)
application.output('MSG: '+ex.getMessage())
if (ex instanceof ServoyException)
{
	/** @type {ServoyException} */
	var servoyException = ex;
	application.output("is a ServoyException")
	application.output("Errorcode: "+servoyException.getErrorCode())
	var trace = "";
	if (ex.getScriptStackTrace) trace = servoyException.getScriptStackTrace();
	else if (servoyException.getStackTrace)  trace = servoyException.getStackTrace();
	if (servoyException.getErrorCode() == ServoyException.SAVE_FAILED)
	{
		plugins.dialogs.showErrorDialog( 'Error',  'It seems you did not fill in a required field',
'OK');
		//Get the failed records after a save
		var array = databaseManager.getFailedRecords()
		for( var i = 0 ; i < array.length ; i++ )
		{
			var record = array[i];
			application.output(record.exception);
			if (record.exception instanceof DataException)
			{
				/** @type {DataException} */
				var dataException = record.exception;
				application.output('SQL: '+dataException.getSQL())
				application.output('SQLState: '+dataException.getSQLState())
				application.output('VendorErrorCode: '+dataException.getVendorErrorCode())
			}
		}
		return false
	}
}
//if returns false or no return, error is not reported to client; if returns true error is reported
//by default error report means logging the error, in smart client an error dialog will also show up
return true
```

SAVE_FAILED

Exception code for SAVE_FAILED.

This code is used when a javascript exception occurred during saving data to the database.

Returns

Number

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//this sample script should be attached to onError method handler in the solution settings
application.output('Exception Object: '+ex)
application.output('MSG: '+ex.getMessage())
if (ex instanceof ServoyException)
{
	/** @type {ServoyException} */
	var servoyException = ex;
	application.output("is a ServoyException")
	application.output("Errorcode: "+servoyException.getErrorCode())
	var trace = "";
	if (ex.getScriptStackTrace) trace = servoyException.getScriptStackTrace();
	else if (servoyException.getStackTrace)  trace = servoyException.getStackTrace();
	if (servoyException.getErrorCode() == ServoyException.SAVE_FAILED)
	{
		plugins.dialogs.showErrorDialog( 'Error',  'It seems you did not fill in a required field',
'OK');
		//Get the failed records after a save
		var array = databaseManager.getFailedRecords()
		for( var i = 0 ; i < array.length ; i++ )
		{
			var record = array[i];
			application.output(record.exception);
			if (record.exception instanceof DataException)
			{
				/** @type {DataException} */
				var dataException = record.exception;
				application.output('SQL: '+dataException.getSQL())
				application.output('SQLState: '+dataException.getSQLState())
				application.output('VendorErrorCode: '+dataException.getVendorErrorCode())
			}
		}
		return false
	}
}
//if returns false or no return, error is not reported to client; if returns true error is reported
//by default error report means logging the error, in smart client an error dialog will also show up
return true
```

UNEXPECTED_UPDATE_COUNT

Exception code for UNEXPECTED_UPDATE_COUNT.

This code is used when a data could not be deleted or updated when expected (for example
when a record was deleted outside Servoy and a Servoy client wants to update the record).

Returns

Number

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//this sample script should be attached to onError method handler in the solution settings
application.output('Exception Object: '+ex)
application.output('MSG: '+ex.getMessage())
if (ex instanceof ServoyException)
{
	/** @type {ServoyException} */
	var servoyException = ex;
	application.output("is a ServoyException")
	application.output("Errorcode: "+servoyException.getErrorCode())
	var trace = "";
	if (ex.getScriptStackTrace) trace = servoyException.getScriptStackTrace();
	else if (servoyException.getStackTrace)  trace = servoyException.getStackTrace();
	if (servoyException.getErrorCode() == ServoyException.SAVE_FAILED)
	{
		plugins.dialogs.showErrorDialog( 'Error',  'It seems you did not fill in a required field',
'OK');
		//Get the failed records after a save
		var array = databaseManager.getFailedRecords()
		for( var i = 0 ; i < array.length ; i++ )
		{
			var record = array[i];
			application.output(record.exception);
			if (record.exception instanceof DataException)
			{
				/** @type {DataException} */
				var dataException = record.exception;
				application.output('SQL: '+dataException.getSQL())
				application.output('SQLState: '+dataException.getSQLState())
				application.output('VendorErrorCode: '+dataException.getVendorErrorCode())
			}
		}
		return false
	}
}
//if returns false or no return, error is not reported to client; if returns true error is reported
//by default error report means logging the error, in smart client an error dialog will also show up
return true
```

UNKNOWN_DATABASE_EXCEPTION

Exception code for UNKNOWN_DATABASE_EXCEPTION.

This code is used when an unrecognized database exception has occurred.

Returns

Number

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//this sample script should be attached to onError method handler in the solution settings
application.output('Exception Object: '+ex)
application.output('MSG: '+ex.getMessage())
if (ex instanceof ServoyException)
{
	/** @type {ServoyException} */
	var servoyException = ex;
	application.output("is a ServoyException")
	application.output("Errorcode: "+servoyException.getErrorCode())
	var trace = "";
	if (ex.getScriptStackTrace) trace = servoyException.getScriptStackTrace();
	else if (servoyException.getStackTrace)  trace = servoyException.getStackTrace();
	if (servoyException.getErrorCode() == ServoyException.SAVE_FAILED)
	{
		plugins.dialogs.showErrorDialog( 'Error',  'It seems you did not fill in a required field',
'OK');
		//Get the failed records after a save
		var array = databaseManager.getFailedRecords()
		for( var i = 0 ; i < array.length ; i++ )
		{
			var record = array[i];
			application.output(record.exception);
			if (record.exception instanceof DataException)
			{
				/** @type {DataException} */
				var dataException = record.exception;
				application.output('SQL: '+dataException.getSQL())
				application.output('SQLState: '+dataException.getSQLState())
				application.output('VendorErrorCode: '+dataException.getVendorErrorCode())
			}
		}
		return false
	}
}
//if returns false or no return, error is not reported to client; if returns true error is reported
//by default error report means logging the error, in smart client an error dialog will also show up
return true
```

Methods Details

getContext()

Returns

String

Supported Clients

SmartClient,WebClient,NGClient

Sample

getErrorCode()

Returns the error code for this ServoyException. Can be one of the constants declared in ServoyException.

Returns

Number the error code for this ServoyException. Can be one of the constants declared in ServoyException.

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//this sample script should be attached to onError method handler in the solution settings
application.output('Exception Object: '+ex)
application.output('MSG: '+ex.getMessage())
if (ex instanceof ServoyException)
{
	/** @type {ServoyException} */
	var servoyException = ex;
	application.output("is a ServoyException")
	application.output("Errorcode: "+servoyException.getErrorCode())
	var trace = "";
	if (ex.getScriptStackTrace) trace = servoyException.getScriptStackTrace();
	else if (servoyException.getStackTrace)  trace = servoyException.getStackTrace();
	if (servoyException.getErrorCode() == ServoyException.SAVE_FAILED)
	{
		plugins.dialogs.showErrorDialog( 'Error',  'It seems you did not fill in a required field',
'OK');
		//Get the failed records after a save
		var array = databaseManager.getFailedRecords()
		for( var i = 0 ; i < array.length ; i++ )
		{
			var record = array[i];
			application.output(record.exception);
			if (record.exception instanceof DataException)
			{
				/** @type {DataException} */
				var dataException = record.exception;
				application.output('SQL: '+dataException.getSQL())
				application.output('SQLState: '+dataException.getSQLState())
				application.output('VendorErrorCode: '+dataException.getVendorErrorCode())
			}
		}
		return false
	}
}
//if returns false or no return, error is not reported to client; if returns true error is reported
//by default error report means logging the error, in smart client an error dialog will also show up
return true
```

getMessage()

Returns the string message for this ServoyException.

Returns

String the string message for this ServoyException.

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//this sample script should be attached to onError method handler in the solution settings
application.output('Exception Object: '+ex)
application.output('MSG: '+ex.getMessage())
if (ex instanceof ServoyException)
{
	/** @type {ServoyException} */
	var servoyException = ex;
	application.output("is a ServoyException")
	application.output("Errorcode: "+servoyException.getErrorCode())
	var trace = "";
	if (ex.getScriptStackTrace) trace = servoyException.getScriptStackTrace();
	else if (servoyException.getStackTrace)  trace = servoyException.getStackTrace();
	if (servoyException.getErrorCode() == ServoyException.SAVE_FAILED)
	{
		plugins.dialogs.showErrorDialog( 'Error',  'It seems you did not fill in a required field',
'OK');
		//Get the failed records after a save
		var array = databaseManager.getFailedRecords()
		for( var i = 0 ; i < array.length ; i++ )
		{
			var record = array[i];
			application.output(record.exception);
			if (record.exception instanceof DataException)
			{
				/** @type {DataException} */
				var dataException = record.exception;
				application.output('SQL: '+dataException.getSQL())
				application.output('SQLState: '+dataException.getSQLState())
				application.output('VendorErrorCode: '+dataException.getVendorErrorCode())
			}
		}
		return false
	}
}
//if returns false or no return, error is not reported to client; if returns true error is reported
//by default error report means logging the error, in smart client an error dialog will also show up
return true
```

getScriptStackTrace()

Returns the script stack trace for this ServoyException if this could be created.

Returns

String the string stack trace for this ServoyException.

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//this sample script should be attached to onError method handler in the solution settings
application.output('Exception Object: '+ex)
application.output('MSG: '+ex.getMessage())
if (ex instanceof ServoyException)
{
	/** @type {ServoyException} */
	var servoyException = ex;
	application.output("is a ServoyException")
	application.output("Errorcode: "+servoyException.getErrorCode())
	var trace = "";
	if (ex.getScriptStackTrace) trace = servoyException.getScriptStackTrace();
	else if (servoyException.getStackTrace)  trace = servoyException.getStackTrace();
	if (servoyException.getErrorCode() == ServoyException.SAVE_FAILED)
	{
		plugins.dialogs.showErrorDialog( 'Error',  'It seems you did not fill in a required field',
'OK');
		//Get the failed records after a save
		var array = databaseManager.getFailedRecords()
		for( var i = 0 ; i < array.length ; i++ )
		{
			var record = array[i];
			application.output(record.exception);
			if (record.exception instanceof DataException)
			{
				/** @type {DataException} */
				var dataException = record.exception;
				application.output('SQL: '+dataException.getSQL())
				application.output('SQLState: '+dataException.getSQLState())
				application.output('VendorErrorCode: '+dataException.getVendorErrorCode())
			}
		}
		return false
	}
}
//if returns false or no return, error is not reported to client; if returns true error is reported
//by default error report means logging the error, in smart client an error dialog will also show up
return true
```

getStackTrace()

Returns the stack trace for this ServoyException.

Returns

String the string stack trace for this ServoyException.

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//this sample script should be attached to onError method handler in the solution settings
application.output('Exception Object: '+ex)
application.output('MSG: '+ex.getMessage())
if (ex instanceof ServoyException)
{
	/** @type {ServoyException} */
	var servoyException = ex;
	application.output("is a ServoyException")
	application.output("Errorcode: "+servoyException.getErrorCode())
	var trace = "";
	if (ex.getScriptStackTrace) trace = servoyException.getScriptStackTrace();
	else if (servoyException.getStackTrace)  trace = servoyException.getStackTrace();
	if (servoyException.getErrorCode() == ServoyException.SAVE_FAILED)
	{
		plugins.dialogs.showErrorDialog( 'Error',  'It seems you did not fill in a required field',
'OK');
		//Get the failed records after a save
		var array = databaseManager.getFailedRecords()
		for( var i = 0 ; i < array.length ; i++ )
		{
			var record = array[i];
			application.output(record.exception);
			if (record.exception instanceof DataException)
			{
				/** @type {DataException} */
				var dataException = record.exception;
				application.output('SQL: '+dataException.getSQL())
				application.output('SQLState: '+dataException.getSQLState())
				application.output('VendorErrorCode: '+dataException.getVendorErrorCode())
			}
		}
		return false
	}
}
//if returns false or no return, error is not reported to client; if returns true error is reported
//by default error report means logging the error, in smart client an error dialog will also show up
return true
```