agent

Feb 20, 2024 09:11

Supported Clients

SmartClient

Property Summary

Number x	Gets or sets the x position of the agent.
Number y	Gets or sets the y position of the agent.

Methods Summary

void	setBalloonSize(width, height)	Sets the size of the balloon.
void	setImageURL(url)	Sets a new image for the agent.
void	setLocation(x, y)	Sets the location of the agent.
void	setVisible(visible)	Show/hides the agent.
void	speak(message)	Makes the agent speak.

Property Details

x

Gets or sets the x position of the agent.

Returns

Number

Supported Clients

SmartClient

Sample

```
//move the agent diagonaly
plugins.agent.x = plugins.agent.x-10;
plugins.agent.y = plugins.agent.y-10;
```

y

Gets or sets the y position of the agent.

Returns

Number

Supported Clients

SmartClient

Sample

```
//move the agent diagonaly
plugins.agent.x = plugins.agent.x-10;
plugins.agent.y = plugins.agent.y-10;
```

Methods Details

setBalloonSize(width, height)

Sets the size of the balloon.

Parameters

Number width ;
Number height ;

Supported Clients

SmartClient

Sample

```
plugins.agent.setBalloonSize(width,height)
```

setImageURL(url)

Sets a new image for the agent.

Parameters

String url ;

Supported Clients

SmartClient

Sample

```
plugins.agent.setImageURL("url")
```

setLocation(x, y)

Sets the location of the agent.

Parameters

Number x ;
Number y ;

Supported Clients

SmartClient

Sample

```
plugins.agent.setLocation(100,100);
```

setVisible(visible)

Show/hides the agent.

Parameters

Boolean visible ;

Supported Clients

SmartClient

Sample

```
plugins.agent.setVisible(true);
```

speak(message)

Makes the agent speak.

Parameters

String message ;

Supported Clients

SmartClient

Sample

```
plugins.agent.speak('hello nerd');
```