


JSConnectionDefinition

 May 04, 2024 12:15

Supported Clients

SmartClient WebClient NGClient

Methods Summary	
JSConnectionDefi create() nition	Registers this JSConnectionDefinition to the server with the current configuration.
void destroy()	Destoyes this JSConnectonDefintion, this unregisters this on the server so it will not use this configuration anymore to create connections.
String password() JSConnectionDefi password(password) nition	returns the password that was set by password(string) Sets the password to use for this client connection.
JSConnectionDefi setProperty(key, value) nition	Set a key value pair that is used as a connection property for this connection definition
String username() JSConnectionDefi username(username) nition	returns the username that was set by username(string) Sets the username to use for this client connection.

Methods Details

create()

Registers this JSConnectionDefinition to the server with the current configuration.
After this call all connections to that database will use the configuration of this definition.

Returns

JSConnectionDefinition The this if it could be created, this will return null if there was a creating this definition (check logs)

Supported Clients

SmartClient,WebClient,NGClient

Sample

destroy()

Destoyes this JSConnectonDefintion, this unregisters this on the server so it will not use this configuration anymore to create connections.

Supported Clients

SmartClient,WebClient,NGClient

Sample

password()

returns the password that was set by password(string)

Returns

String the password for this connection.

Supported Clients

SmartClient,WebClient,NGClient

Sample

password(password)

Sets the password to use for this client connection.

Parameters

String password ;

Returns

JSConnectionDefinition this

Supported Clients

SmartClient,WebClient,NGClient

Sample**setProperty(key, value)**

Set a key value pair that is used as a connection property for this connection definition

Parameters

[String](#) key The propertie key
[String](#) value The property value

Returns

[JSConnectionDefinition](#) this

Supported Clients

SmartClient,WebClient,NGClient

Sample**username()**

returns the username that was set by username(string)

Returns

[String](#) the username for this connection.

Supported Clients

SmartClient,WebClient,NGClient

Sample**username(username)**

Sets the username to use for this client connection.

Parameters

[String](#) username ;

Returns

[JSConnectionDefinition](#) this

Supported Clients

SmartClient,WebClient,NGClient

Sample