

QBCase

 Apr 17, 2024 17:53

Supported Clients

SmartClient WebClient NGClient

Property Summary

[QBTableClause](#) [parent](#) Get query builder parent table clause, this may be a query or a join clause.
[QBSelect](#) [root](#) Get query builder parent.

Methods Summary

[QBColumn](#) [else\(value\)](#) Set the return value to use when none of the when-clauses conditions are met.
[QBCaseWhen](#) [when\(condition\)](#) Add a when-clause to the case searched expression.

Property Details

parent

Get query builder parent table clause, this may be a query or a join clause.

Returns

[QBTableClause](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var query = datasources.db.example_data.person.createSelect();
query.where.add(query.joins.person_to_parent.joins.person_to_parent.columns.name.eq('john'))
foundset.loadRecords(query)
```

root

Get query builder parent.

Returns

[QBSelect](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var subquery = datasources.db.example_data.order_details.createSelect();

var query = datasources.db.example_data.orders.createSelect();
query.where.add(query
    .or
        .add(query.columns.order_id.not.isin([1, 2, 3]))
        .add(query.exists(
            subquery.where.add(subquery.columns.orderid.eq(query.columns.order_id)).
root
        ))
    )

foundset.loadRecords(query)
```

Methods Details

else(value)

Set the return value to use when none of the when-clauses conditions are met.

Parameters

[Object](#) value The value.

Returns

[QBColumn](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var query = datasources.db.example_data.order_details.createSelect();

// case expressions can be added to the result of the query
query.result.add(query.case.when(query.columns.quantity.ge(1000)).then('BIG').else('small'));

// they can also be used in conditions
query.where.add(query.case
    .when(query.columns.discount.gt(10)).then(50)
    .when(query.columns.quantity.le(20)).then(70)
    .else(100)
    .multiply(query.columns.unitprice).lt(10000));
```

when(condition)

Add a when-clause to the case searched expression.

Parameters

[QBCondition](#) condition The condition.

Returns

[QBCaseWhen](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var query = datasources.db.example_data.order_details.createSelect();

// case expressions can be added to the result of the query
query.result.add(query.case.when(query.columns.quantity.ge(1000)).then('BIG').else('small'));

// they can also be used in conditions
query.where.add(query.case
    .when(query.columns.discount.gt(10)).then(50)
    .when(query.columns.quantity.le(20)).then(70)
    .else(100)
    .multiply(query.columns.unitprice).lt(10000));
```