


Table

 Apr 06, 2024 16:59

Supported Clients

SmartClient WebClient NGClient

Property Summary

Object columns

| Event Summary | | |
|---------------|--|---|
| void | onAfterCreate(record) | A method that is executed after a new record is created. |
| void | onAfterDelete(record) | A method that is executed after a delete operation. |
| void | onAfterFind() | A method that is executed after a foundset has switched to find mode. |
| void | onAfterInsert(record) | A method that is executed after an insert operation. |
| void | onAfterSearch() | A method that is executed after a search is executed for a foundset. |
| void | onAfterUpdate(record) | A method that is executed after an update operation. |
| Boolean | onCreate() | A method that is executed before a record is created. |
| Boolean | onDelete(record) | A method that is executed before a delete operation. |
| Boolean | onFind() | A method that is executed before a foundset is going into find mode. |
| void | onFoundSetLoad(memOrViewName) | A method that is executed when an in memory or viewfoundset table is first touched (by ui or scripting) |
| JSDataSet | onFoundsetNextChunk(inmemDataSourceName, sizeHint) | A method that can be used to load extra data in an in memory datasource. |
| Boolean | onInsert(record, recordMarkers, stateObject) | A method that is executed before an insert operation. |
| Boolean | onSearch(clearLastResults, reduceSearch) | A method that is executed before search() is called on a foundset in find mode. |
| Boolean | onUpdate(record, recordMarkers, stateObject) | A method that is executed before an update operation. |
| void | onValidate(record, recordMarkers, stateObject) | A method that is executed before an insert operation. |

Property Details

columns

Returns

Object

Supported Clients

SmartClient,WebClient,NGClient

Sample

Event Details

onAfterCreate(record)
A method that is executed after a new record is created.

Parameters

[JSRecord](#) record record that is created

Supported Clients

SmartClient,WebClient,NGClient

Sample

onAfterDelete(record)
A method that is executed after a delete operation.

Parameters

[JSRecord](#) record record that is deleted

Supported Clients

SmartClient,WebClient,NGClient

Sample
onAfterFind()

A method that is executed after a foundset has switched to find mode.

Supported Clients

SmartClient,WebClient,NGClient

Sample
onAfterInsert(record)

A method that is executed after an insert operation.

Parameters

[JSRecord](#) record record that is inserted

Supported Clients

SmartClient,WebClient,NGClient

Sample
onAfterSearch()

A method that is executed after a search is executed for a foundset.

Supported Clients

SmartClient,WebClient,NGClient

Sample
onAfterUpdate(record)

A method that is executed after an update operation.

Parameters

[JSRecord](#) record record that is updated

Supported Clients

SmartClient,WebClient,NGClient

Sample
onCreate()

A method that is executed before a record is created. The method can block the creation by returning false.

Returns

[Boolean](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample
onDelete(record)

A method that is executed before a delete operation. The method can block the delete operation by returning false.

Parameters

[JSRecord](#) record record that will be deleted

Returns

[Boolean](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample**onFind()**

A method that is executed before a foundset is going into find mode. The method can block the mode change.

Returns

[Boolean](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample**onFoundSetLoad(memOrViewName)**

A method that is executed when an in memory or viewfoundset table is first touched (by ui or scripting)

Parameters

[String](#) memOrViewName The in memory or view foundset table name that is touched.

Supported Clients

SmartClient,WebClient,NGClient

Sample**onFoundsetNextChunk(inmemDataSourceName, sizeHint)**

A method that can be used to load extra data in an in memory datasource.

<p>

This method id called when the inMem datasource is fully read.

Parameters

[String](#) inmemDataSourceName name of the inmemory datasource.

[Number](#) sizeHint preferred number of records to be retrieved.

Returns

[JSDataSet](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample**onInsert(record, recordMarkers, stateObject)**

A method that is executed before an insert operation. The method can block the insert operation by returning false.

Parameters

[JSRecord](#) record record that will be inserted

[JSRecordMarkers](#) recordMarkers the object where all the problems can be reported against

[Object](#) stateObject an object that a user can give to validateRecord for extra state (optional, can be null).

Returns

[Boolean](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample**onSearch(clearLastResults, reduceSearch)**

A method that is executed before search() is called on a foundset in find mode. The method can block the search (foundset will stay in find mode).

Parameters

[Boolean](#) clearLastResults ;

[Boolean](#) reduceSearch ;

Returns[Boolean](#)**Supported Clients**

SmartClient,WebClient,NGClient

Sample**onUpdate(record, recordMarkers, stateObject)**

A method that is executed before an update operation. A method can block the update by returning false.

Parameters

| | | |
|---------------------------------|---------------|---|
| JSRecord | record | record that will be updated |
| JSRecordMarkers | recordMarkers | the object where all the problems can be reported against |
| Object | stateObject | an object that a user can give to validateRecord for extra state (optional, can be null). |

Returns[Boolean](#)**Supported Clients**

SmartClient,WebClient,NGClient

Sample**onValidate(record, recordMarkers, stateObject)**

A method that is executed before an insert operation. The method can block the insert operation by returning false.

Parameters

| | | |
|---------------------------------|---------------|---|
| JSRecord | record | record that must be validated |
| JSRecordMarkers | recordMarkers | the object where all the problems can be reported against. |
| Object | stateObject | an object that a user can give to validateRecord for extra state (optional, can be null). |

Supported Clients

SmartClient,WebClient,NGClient

Sample