

JSAuthenticateRequest

Method Summary

void [addAttributeRequest](#)(alias, schemaURI, required)
Add attribute request

void [execute](#)()

Method Details

addAttributeRequest

void **addAttributeRequest** (alias, schemaURI, required)
Add attribute request

Parameters

[{String}](#) alias
[{String}](#) schemaURI
[{Boolean}](#) required

Returns

void

Sample

```
authenticateRequest.addAttributeRequest('email', 'http://axschema.org/contact/email', true);
```

execute

void **execute** ()

Returns

void

Sample

```
var authenticateRequest = plugins.openid.createAuthenticateRequest('https://www.google.com/accounts/o8/id',
openIDLoginCallback);
authenticateRequest.addAttributeRequest('email', 'http://axschema.org/contact/email', true);
//see http://www.axschema.org/types/ for more attributes, not all are supported by all providers!
authenticateRequest.execute();

//sample
//function openIDLoginCallback(identifier, authenticateResult)
//{
//    var ok = false;
//    if (identifier)
//    {
//        var id = identifier.substring(identifier.lastIndexOf('=')+1)
//        application.output('id:'+id)
//        var email = authenticateResult.getAttributeValue('email')
//        application.output('email:'+email)
//        ok = security.login(email, id, ['Administrators'])
//    }
//    if (!ok)
//    {
//        application.output('Login failed')
//    }
//}
```