

# RuntimeBean

## Extends

[RuntimeComponent](#)

## Property Summary

<a href="#">Boolean</a>	<a href="#">enabled</a> Gets or sets the enabled state of a specified field, also known as "grayed".
<a href="#">String</a>	<a href="#">innerHTML</a> Gets or sets the innerHTML that is displayed on the bean's div
<a href="#">Boolean</a>	<a href="#">visible</a> Gets or sets the visibility of an element; true - visible; false - not visible; ! - the visibility state is inverted (the opposite).

## Method Summary

<a href="#">String</a>	<a href="#">getName()</a> Returns the name of an element.
------------------------	--

## Property Details

### enabled

Gets or sets the enabled state of a specified field, also known as "grayed".  
true - enabled; false - not enabled; ! - the enabled state is inverted (the opposite).

NOTE: A disabled element cannot be selected by clicking the element (or by pressing the TAB key even if this option is supported by the operating system).

NOTE: A label or button element will not disable if the "displayType" design time property for a field is set to HTML\_AREA.

NOTE: The disabled "grayed" color is dependent on the LAF set in the Servoy Client Application Preferences. For more information see Preferences: Look And Feel in the Servoy Developer User's Guide.

### Returns

[Boolean](#)

### Sample

```
//gets the enabled state of the field
var currState = forms.customer.elements.customer_id.enabled;

//sets the enabled state of the field
forms.customer.elements.customer_id.enabled = !currentState;
```

### innerHTML

Gets or sets the innerHTML that is displayed on the bean's div

### Returns

[String](#)

### Sample

```
//gets the innerHTML of the element
var my_bean_innerHTML = forms.customer.elements.customer_id.innerHTML;

//sets the innerHTML of the element
forms.customer.elements.customer_id.innerHTML = '<div>my inner HTML</div>';
```

### visible

Gets or sets the visibility of an element; true - visible; false - not visible; ! - the visibility state is inverted (the opposite).

NOTE: The visibility of an element is not persistent; the state of visibility only applies to the current user in his/her current session.

#### Returns

Boolean

### Sample

```
//sets the element as visible
forms.company.elements.faxBtn.visible = true;

//gets the visibility of the element
var currentState = forms.company.elements.faxBtn.visible;

//sets the element as not visible when the current state is visible
forms.company.elements.faxBtn.visible = !currentState;
```

### Method Details

#### getName

[String](#) **getName()**

Returns the name of an element. (may be null as well)

#### Returns

[String](#) - The name of the element.

### Sample

```
var name = forms.customer.elements.customer_id.getName();
```