

dialogs

 Apr 03, 2024 05:21

Supported Clients

SmartClient WebClient NGClient MobileClient

Methods Summary		
String	showErrorDialog(dialogTitle, dialogMessage, buttonsText)	Shows a message dialog with the specified title, message and a customizable set of buttons.
String	showInfoDialog(dialogTitle, dialogMessage, buttonsText)	Shows a message dialog with the specified title, message and a customizable set of buttons.
String	showInputDialog()	Shows an input dialog where the user can enter data.
String	showInputDialog(dialog_title)	Shows an input dialog where the user can enter data.
String	showInputDialog(dialog_title, msg)	Shows an input dialog where the user can enter data.
String	showInputDialog(dialog_title, msg, initialValue)	Shows an input dialog where the user can enter data.
String	showQuestionDialog(dialogTitle, dialogMessage, buttonsText)	Shows a message dialog with the specified title, message and a customizable set of buttons.
String	showSelectDialog(dialog_title, msg, optionArray)	Shows a selection dialog, where the user can select an entry from a list of options.
String	showSelectDialog(dialog_title, msg, options)	Shows a selection dialog, where the user can select an entry from a list of options.
String	showWarningDialog(dialogTitle, dialogMessage, buttonsText)	Shows a message dialog with the specified title, message and a customizable set of buttons.

Methods Details

showErrorDialog(dialogTitle, dialogMessage, buttonsText)

Shows a message dialog with the specified title, message and a customizable set of buttons.
Returns pressed button text, in case window is closed without pressing any button return value depends on client type.

Parameters

String dialogTitle

Dialog title.

String dialogMessage

Dialog message.

Array buttonsText

Array of button texts.

Returns

String

pressed button text

Supported Clients

SmartClient,WebClient,NGClient

Sample

//show dialog
var thePressedButton = plugins.dialogs.showErrorDialog('Title', 'Value not allowed','OK');

showInfoDialog(dialogTitle, dialogMessage, buttonsText)

Shows a message dialog with the specified title, message and a customizable set of buttons.
Returns pressed button text, in case window is closed without pressing any button return value depends on client type.

Parameters

String dialogTitle

Dialog title.

String dialogMessage

Dialog message.

Array buttonsText

Array of button texts.

Returns

String

pressed button text

Supported Clients

SmartClient,WebClient,NGClient

Sample

//show dialog
var thePressedButton = plugins.dialogs.showInfoDialog('Title', 'Value not allowed','OK');

showInputDialog()

Shows an input dialog where the user can enter data. Returns the entered data, or nothing when canceled.

Returns

[String](#) input text or null

Supported Clients

SmartClient, WebClient, NGClient

Sample

```
//show input dialog ,returns nothing when canceled
var typedInput = plugins.dialogs.showInputDialog('Specify','Your name');
```

showInputDialog(dialog_title)

Shows an input dialog where the user can enter data. Returns the entered data, or nothing when canceled.

Parameters

[String](#) dialog_title;

Returns

[String](#) input text or null

Supported Clients

SmartClient, WebClient, NGClient

Sample

```
//show input dialog ,returns nothing when canceled
var typedInput = plugins.dialogs.showInputDialog('Specify','Your name');
```

showInputDialog(dialog_title, msg)

Shows an input dialog where the user can enter data. Returns the entered data, or nothing when canceled.

Parameters

[String](#) dialog_title;

[String](#) msg;

Returns

[String](#) input text or null

Supported Clients

SmartClient, WebClient, NGClient

Sample

```
//show input dialog ,returns nothing when canceled
var typedInput = plugins.dialogs.showInputDialog('Specify','Your name');
```

showInputDialog(dialog_title, msg, initialValue)

Shows an input dialog where the user can enter data. Returns the entered data, or nothing when canceled.

Parameters

[String](#) dialog_title;

[String](#) msg;

[String](#) initialValue;

Returns

[String](#) input text or null

Supported Clients

SmartClient, WebClient, NGClient

Sample

```
//show input dialog ,returns nothing when canceled
var typedInput = plugins.dialogs.showInputDialog('Specify','Your name');
```

showQuestionDialog(dialogTitle, dialogMessage, buttonsText)

Shows a message dialog with the specified title, message and a customizable set of buttons. Returns pressed button text, in case window is closed without pressing any button return value depends on client type.

Parameters

`String` dialogTitle Dialog title.
`String` dialogMessage Dialog message.
`Array` buttonsText Array of button texts.

Returns

`String` pressed button text

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//show dialog
var thePressedButton = plugins.dialogs.showQuestionDialog('Title', 'Value not allowed','OK');
```

showSelectDialog(dialog_title, msg, optionArray)

Shows a selection dialog, where the user can select an entry from a list of options. Returns the selected entry, or nothing when canceled.

Parameters

`String` dialog_title ;
`String` msg ;
`Array` optionArray;

Returns

`String` selected value or null

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//show select,returns nothing when canceled
var selectedValue = plugins.dialogs.showSelectDialog('Select','please select a name','jan','johan','sebastiaan');
//also possible to pass array with options
//var selectedValue = plugins.dialogs.showSelectDialog('Select','please select a name', new Array
('jan','johan','sebastiaan'));
```

showSelectDialog(dialog_title, msg, options)

Shows a selection dialog, where the user can select an entry from a list of options. Returns the selected entry, or nothing when canceled.

Parameters

`String` dialog_title ;
`String` msg ;
`Array` options ;

Returns

`String` selected value or null

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//show select,returns nothing when canceled
var selectedValue = plugins.dialogs.showSelectDialog('Select','please select a name','jan','johan','sebastiaan');
//also possible to pass array with options
//var selectedValue = plugins.dialogs.showSelectDialog('Select','please select a name', new Array
('jan','johan','sebastiaan'));
```

showWarningDialog(dialogTitle, dialogMessage, buttonsText)

Shows a message dialog with the specified title, message and a customizable set of buttons. Returns pressed button text, in case window is closed without pressing any button return value depends on client type.

Parameters

`String` dialogTitle Dialog title.
`String` dialogMessage Dialog message.
`Array` buttonsText Array of button texts.

Returns

`String` pressed button text

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//show dialog  
var thePressedButton = plugins.dialogs.showWarningDialog('Title', 'Value not allowed','OK');
```