

JSDataSource



Apr 16, 2024 18:49

Supported Clients

SmartClient WebClient NGClient

Methods Summary

QBSelect	createSelect()	Create a query builder for a data source.
QBSelect	createSelect(tableAlias)	Create a query builder for a data source with given table alias.
Array	getColumnNames()	Get the column names of a datasource.
String	getDataSource()	Get the datasource string.
JSFoundSet	getFoundSet()	Returns a foundset object for a specified datasource or server and tablename.
JSFoundSet	getFoundSet(name)	An existing foundset under that name will be returned, or created if there is a definition (there is a form with a named foundset property with that name).
JSRecord	getRecord(pk)	Get a single record from a datasource.
JSTable	getTable()	Get the table of a datasource.
JSFoundSet	loadRecords(dataset)	get a new foundset containing records based on a dataset of pks.
JSFoundSet	loadRecords(qbSelect)	get a new foundset containing records based on a QBSelect query.
JSFoundSet	loadRecords(query)	get a new foundset containing records based on an SQL query string.
JSFoundSet	loadRecords(query, args)	get a new foundset containing records based on an SQL query string with parameters.

Methods Details

createSelect()
Create a query builder for a data source.

Returns

QBSelect query builder

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var q = datasources.db.example_data.book_nodes.createSelect()  
q.result.addPk()  
q.where.add(q.columns.label_text.not.isIn(null))  
datasources.db.example_data.book_nodes.getFoundSet().loadRecords(q)
```

createSelect(tableAlias)
Create a query builder for a data source with given table alias.
The alias can be used inside custom queries to bind to the outer table.

Parameters

String tableAlias the table alias to use

Returns

QBSelect query builder

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var q = datasources.db.example_data.book_nodes.createSelect('b')  
q.result.addPk()  
q.where.add(q.columns.label_text.isIn('select comment_text from book_text t where t.note_text = ? and t.node_id  
= b.node_id', ['test']))  
datasources.db.example_data.book_nodes.getFoundSet().loadRecords(q)
```

getColumnNames()
Get the column names of a datasource.

Returns

Array String[] column names

Supported Clients

SmartClient,WebClient,NGClient

Sample**getDataSource()**

Get the datasource string.

Returns[String](#) String datasource**Supported Clients**

SmartClient,WebClient,NGClient

Sample

```
datasources.db.example_data.orders.getDataSource() // returns 'db:/example_data/orders'
```

getFoundSet()

Returns a foundset object for a specified datasource or server and tablename.
It is important to note that this is a FACTORY method, it constantly creates new foundsets.

Returns[JSFoundSet](#) A new JSFoundset for the datasource.**Supported Clients**

SmartClient,WebClient,NGClient

Sample

```
var fs = datasources.db.example_data.orders.getFoundSet()
var ridx = fs.newRecord()
var record = fs.getRecord(ridx)
record.emp_name = 'John'
databaseManager.saveData()
```

getFoundSet(name)

An existing foundset under that name will be returned, or created if there is a definition (there is a form with a named foundset property with that name).
If named foundset datasource does not match current datasource will not be returned (will return null instead).

Parameters[String](#) name The named foundset to get for this datasource.**Returns**[JSFoundSet](#) An existing named foundset for the datasource.**Supported Clients**

SmartClient,WebClient,NGClient

Sample

```
var fs = datasources.db.example_data.orders.getFoundSet('myname')
var ridx = fs.newRecord()
var record = fs.getRecord(ridx)
record.emp_name = 'John'
databaseManager.saveData()
```

getRecord(pk)

Get a single record from a datasource.
For the sake of performance, if more records are needed,
don't call this method in a loop but try using other methods instead.

Parameters[Object](#) pk The primary key of the record to be retrieved. Can be an array, in case of a composite pk.**Returns**[JSRecord](#) a record

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var detailsRecord = datasources.db.example_data.order_details.getRecord([10248, 11])
var orderRecord = datasources.db.example_data.orders.getRecord(10248)
var customerRecord = datasources.db.example_data.customers.getRecord('ANATR')
```

getTable()

Get the table of a datasource.

Returns[JSTable](#) JSTable table**Supported Clients**

SmartClient,WebClient,NGClient

Sample**loadRecords(dataSet)**

get a new foundset containing records based on a dataset of pks.

Parameters[JSDataSet](#) dataSet;**Returns**[JSFoundSet](#) a new JSFoundset**Supported Clients**

SmartClient,WebClient,NGClient

Sample

```
var fs = datasources.db.example_data.customers.loadRecords(pkDataSet)
```

loadRecords(qbSelect)

get a new foundset containing records based on a QBSelect query.

Parameters[QBSelect](#) qbSelect a query builder object**Returns**[JSFoundSet](#) a new JSFoundset**Supported Clients**

SmartClient,WebClient,NGClient

Sample

```
var qb = datasources.db.example_data.orders.createSelect();
qb.result.add(qb.columns.orderid);
var fs = datasources.db.example_data.orders.loadRecords(qb);
```

loadRecords(query)

get a new foundset containing records based on an SQL query string.

Parameters[String](#) query an SQL query**Returns**[JSFoundSet](#) a new JSFoundset**Supported Clients**

SmartClient,WebClient,NGClient

Sample

```
var query = "SELECT * FROM public.orders WHERE customerid = 'ROMEY' ORDER BY orderid ASC";  
var fs = datasources.db.example_data.orders.loadRecords(query);
```

loadRecords(query, args)

get a new foundset containing records based on an SQL query string with parameters.

Parameters

[String](#) query an SQL query string with parameter placeholders

[Array](#) args an array of arguments for the query string

Returns

[JSFoundSet](#) a new JSFoundset

Supported Clients

SmartClient, WebClient, NGClient

Sample

```
var query = "SELECT * FROM public.orders WHERE customerid = ? OR customerid = ? order by orderid asc";  
var args = ['ROMEY', 'BERGS'];  
var fs = datasources.db.example_data.orders.loadRecords(query, args);
```