

Customizing the NG Client

NOTE: this does not work for the Titanium NGClient

The following NG Client html templates can be customized by placing them in a **templates** folder in ROOT (application_server/server/webapps):

1. dialog.html

Dialog template example

```
<div class="svy-dialog" svy-window sablo-tabseq='1' sablo-tabseq-config="{container: true}"
bindonce bo-class="{ 'window':!isUndecorated(), '{{win.cssClassName}}':win.cssClassName}"
bo-style="{ 'background-color':win.transparent ?
'transparent':'inherit'}" >
  <div bo-style="{ 'opacity':win.opacity}">
    <div class='window-header'
      bo-style="{ 'display':isUndecorated()? 'none':'block'}" tabindex="-1"
      style="outline:0;">
      <button type="button" class="svy-dialog-close"
        ng-click="cancel()"
        aria-hidden="true" tabindex="-1">x</button>
      <h4 class="window-title" ng-bind='win.title'></h4>
    </div>
    <div class="window-body"
      bo-style="getBodySize()">
      <div ng-if="win.navigatorForm.name" ng-style="{ 'width':win.navigatorForm.size.
width+'px'}"
        ng-include="getNavigatorFormUrl()" unwanted-dialog-scrollbars-
workaround></div>
      <div id="tabStart" sablo-tabseq='1' ng-focus="firstElementFocused()"><
/div>
      <div sablo-tabseq='2' sablo-tabseq-config="{container: true}" ng-include="
getFormUrl()"
        ng-style="
{'position':'absolute','top':'0px','right':'0px','bottom':'0px','left':win.navigatorForm.size.width+'px'}"
unwanted-dialog-scrollbars-workaround></div>
      <div id="tabStop" sablo-tabseq='3' ng-focus="lastElementFocused()"><
/div>
    </div>
    <div class="window-footer"
      bo-style="{ 'display':isUndecorated()? 'none':'block'}"></div>
  </div>
</div>
```

2. login.html

Login template example

```

<div class="modal-header">
    
</div>
<div class="modal-body">
    <h3 class="svy-login-title">Please sign in</h3>
    <h5 class="svy-login-text-danger">{{model.message}}</h5>
    <form accept-charset="UTF-8" role="form" ng-submit="doLogin()">
        <fieldset class="svy-login-fieldset">
            <div class="svy-login-form-group">
                <input class="svy-login-form-control" placeholder="Username" type="text" ng-model="
model.username">
            </div>
            <div class="svy-login-form-group">
                <input class="svy-login-form-control" placeholder="Password" type="password"
ng-model="model.password">
            </div>
            <div class="checkbox">
                <label>
                    <input name="remember" type="checkbox" value="Remember Me" ng-model="model.
remember"> Remember me
                </label>
            </div>
            <input class="svy-btn svy-btn-success svy-btn-block" type="submit" value="Login">
        </fieldset>
    </form>
</div>

```

3. maintenanceView.html

Maintenance page example

```

<div style='padding:40px;' ng-controller="MaintenanceModeController">
    <div class="bs-callout bs-callout-warning" >
        <h4>The server is in maintenance mode</h4>
        <p>The server is in maintenance mode; please try again later.</p>
        <p><a ng-href="{{redirectUrl}}">Return to home page</a></p>
    </div>
</div>

```

4. notSupportedBrowser.html

Not supported browser page example

```

<html>
<head>
    <link rel="stylesheet" href="/css/bootstrap/css/bootstrap.css"/>
    <link rel="stylesheet" href="/css/servoy.css"/>
</head>
<body>
<div style='padding:40px;'>
    <div class="bs-callout bs-callout-danger" >
        <h4>Page cannot be displayed</h4>
        <p>You are using an old, unsupported browser version.</p>
    </div>
</div>
</body>
</html>

```

5. serverInternalErrorView.html

NG Client Error page example

```
<div style='padding:40px;' ng-controller="InternalServerErrorController">
  <div class="bs-callout bs-callout-danger" >
    <h1>Internal Server error </h1>
    <p>There was an error at the server side</p>
    <pre ng-if='error.stack' ng-bind='error.stack'></pre>
  </div>
</div>
```

6. serverTooBusyView.html

Server too busy page

```
<div style='padding:40px;' ng-controller='NoLicenseController' >
  <div class="bs-callout bs-callout-danger" >
    <h1>The server is too busy</h1>
    <p>The server is too busy; please try again later.</p>
    <p><a ng-href="{{redirectUrl}}">Return to home page</a></p>
  </div>
</div>
```

7. sessionExpiredView.html

NG Client Page expired example

```
<div style='padding:40px;' ng-controller="SessionExpiredController">
  <div class="bs-callout bs-callout-danger" >
    <h1>Page Expired</h1>
    <p>The page you requested has expired.</p>
    <p><a ng-href="{{redirectUrl}}">Return to home page</a></p>
  </div>
</div>
```

8. upload.html

Upload dialog example

```
<div class="svy-upload">
  <h4 class="svy-upload-header-txt">{{getTitleText()}}</h4>
  <table class="svy-upload-table" ng-if="isFileSelected()">
    <caption>{{::i18n_selectedFiles}}</caption>
    <thead><tr><th>{{::i18n_name}}</th><th></th></tr></thead>
    <tr ng-repeat="f in getUploadFiles()"><td>{{f.name}}</td><td><div class="svy-btn svy-btn-
danger" ng-click="doRemove(f)">{{::i18n_remove}}</div></td></tr>
  </table>
  <div ng-if="!isFileSelected()"><span>{{::i18n_nothingSelected}}</span></div>
  <br>
  <div class="svy-btn svy-btn-primary" ngf-select ng-model="uploadFiles" ngf-multiple="
isMultiSelect()">{{::i18n_chooseFiles}}</div>
  <div class="svy-btn svy-btn-success" ng-click="doUpload()">{{::i18n_upload}}</div>
  <div class="svy-btn svy-btn-info" ng-click="dismiss()">{{::i18n_cancel}}</div>
  <br><br>
  <div class="svy-progress">
    <div class="svy-progress-bar" role="progressbar" aria-valuenow="{{getProgress('')}}" aria-
valuemin="0" aria-valuemax="100" style="width: {{getProgress('%')}}">
      {{getProgress('%')}}
    </div>
  </div>
  <div><strong>{{errorText}}</strong></div>
</div>
```