

RuntimeDataLabel

Extends

[RuntimeComponent](#)

Property Summary

String	bgcolor Gets or sets the background color of a field.
String	border Gets or sets the border attribute(s) of a specified element.
Boolean	enabled Gets or sets the enabled state of a specified field, also known as "grayed".
String	fgcolor Gets or sets the foreground color of a field.
String	font Gets or sets the font name, style, and size of an element.
String	format Gets or sets the display formatting of an element for number and text values; does not affect the actual value stored in the database column.
String	imageUrl Gets/Sets the image displayed on a button or label; based on URL.
String	mnemonic Gets or sets the specified character(s) - typically an underlined letter- used with/without the modifier key(s) for the label, button or image.
String	rolloverImageUrl Gets/Sets the image displayed on a button or label roll over; based on URL.
String	toolTipText Gets or sets the tool tip text of an element; text displays when the mouse cursor hovers over an element.
Boolean	transparent Gets or sets the transparency of an element; true - transparent; false - not transparent.
Boolean	visible Gets or sets the visibility of an element; true - visible; false - not visible; ! - the visibility state is inverted (the opposite).

Method Summary

Number	getAbsoluteFormLocationY() Returns the absolute form (designed) Y location.
Object	getClientProperty(key) Gets the specified client property for the element based on a key.
String	getDataProviderID() Get the data provider this UI element (display) is showing.
Object	getDesignTimeProperty() Get a design-time property of an element.
String	getElementType() Returns the type of a specified element.
Number	getHeight() Returns the height of the current element.
String	getLabelForElementName() Gets the label for property of a label.
Number	getLocationX() Returns the x location of the current element.
Number	getLocationY() Returns the y location of the current element.
String	getName() Returns the name of an element.
byte[]	getThumbnailJPGImage() Returns the image data in .
byte[]	getThumbnailJPGImage(width, height) Returns the image data in .
Number	getWidth() Returns the width of the current element.
void	putClientProperty(key, value) Sets the value for the specified element client property key.
void	setLocation(x, y) Sets the location of an element.

void [setSize](#)(width, height)
Sets the size of an element.

Property Details

bgcolor

Gets or sets the background color of a field. The color has to be set using the hexadecimal RGB value as used in HTML. It only returns it's correct value if it was explicitly set.

Returns

[String](#)

Sample

```
//sets the background color of the field
forms.customer.elements.customer_id bgcolor = "#FFFFFF";
//gets the background color of the field
var c = forms.customer.elements.customer_id bgcolor;
```

border

Gets or sets the border attribute(s) of a specified element.

The border attributes:

borderType - EmptyBorder, EtchedBorder, BevelBorder, LineBorder, TitleBorder, MatteBorder, SpecialMatteBorder.
size - (numeric value) for: bottom, left, right, top.
color - (hexadecimal value) for: bottom, left, right, top.
dash pattern - (numeric value) for selected side(s).
rounding radius - (numeric value) for selected side(s).

It only returns it's correct value if it was explicitly set.

NOTE: Use the same value(s) and order of attribute(s) from the element design time property "borderType".

Returns

[String](#)

Sample

```
//sets the border type to "LineBorder"
//sets a 1 px line width for the bottom and left side of the border
//sets the hexadecimal color of the border to "#ccffcc"
forms.customer.elements.customer_id.border = 'LineBorder,1,#ccffcc';
```

enabled

Gets or sets the enabled state of a specified field, also known as "grayed".
true - enabled; false - not enabled; ! - the enabled state is inverted (the opposite).

NOTE: A disabled element cannot be selected by clicking the element (or by pressing the TAB key even if this option is supported by the operating system).

NOTE: A label or button element will not disable if the "displayType" design time property for a field is set to HTML_AREA.

NOTE: The disabled "grayed" color is dependent on the LAF set in the Servoy Client Application Preferences. For more information see Preferences: Look And Feel in the Servoy Developer User's Guide.

Returns

[Boolean](#)

Sample

```
//gets the enabled state of the field
var currState = forms.customer.elements.customer_id.enabled;

//sets the enabled state of the field
forms.customer.elements.customer_id.enabled = !currentState;
```

fgcolor

Gets or sets the foreground color of a field. The color has to be set using the hexadecimal RGB value as used in HTML. It only returns its correct value if it was explicitly set.

Returns

[String](#)

Sample

```
//sets the foreground color of the field
forms.customer.elements.customer_id.fgcolor = "#000000";

//gets the foreground color of the field
var c = forms.customer.elements.customer_id.fgcolor;
```

font

Gets or sets the font name, style, and size of an element.

font name - the name of the font family.

style - the type of the font. (plain = 0; bold = 1; italic = 2; bold-italic = 3).

size - the size of the font (in points).

It only returns its correct value if it was explicitly set.

Returns

[String](#)

Sample

```
forms.customer.elements.customer_id.font = 'Tahoma,1,11';
```

format

Gets or sets the display formatting of an element for number and text values; does not affect the actual value stored in the database column.

There are different options for the different dataprovider types that are assigned to this field.

For Integer fields, there is a display and an edit format, using <http://docs.oracle.com/javase/7/docs/api/java/text/DecimalFormat.html> and the max (string) length can be set.

For Text/String fields, there are options to force uppercase, lowercase or only numbers. Or a mask can be set that restrict the input the pattern chars can be found here: <http://docs.oracle.com/javase/7/docs/api/javawx/swing/text/MaskFormatter.html>

A mask can have a placeholder (what is shown when there is no data) and if the data must be stored raw (without literals of the mask). A max text length can also be set to force

the max text length input, this doesn't work on mask because that max length is controlled with the mask.

For Date fields a display and edit format can be set by using a pattern from here: <http://docs.oracle.com/javase/7/docs/api/java/text/SimpleDateFormat.html>, you can also say this must behave like a mask (the edit format)

A mask only works with when the edit format is exactly that mask (1 char is 1 number/char), because for example MM then only 2 numbers are allowed MMM that displays the month as a string is not supported as a mask.

Some examples are "dd-MM-yyyy", "MM-dd-yyyy", etc.

The format property is also used to set the UI Converter, this means that you can convert the value object to something else before it gets set into the field, this can also result in a type change of the data.

So a string in scripting/db is converted to an integer in the ui, then you have to set an integer format.

It only returns its correct value if it was explicitly set, otherwise null.

Returns

[String](#)

Sample

```
//sets the display formatting of the field
forms.customer.elements.customer_id.format = '###';

//gets the display formatting of the field
var format = forms.customer.elements.customer_id.format;
```

imageUrl

Gets/Sets the image displayed on a button or label; based on URL.

Returns

[String](#)

Sample

```
//dynamically sets an image displayed on a button or label
forms.customer.elements.customer_id.imageUrl = "http://www.servoy.com/images/test.gif";

//sets an image from your own image library
forms.customer.elements.customer_id.imageUrl = "media:///arrow.gif";

//loads an image (BLOB) from a field in a selected record into HTML
forms.customer.elements.customer_id.imageUrl = 'media:///servoy_blobloader?datasource='+controller.
getDataSource()+'&datapvider=image_data&mimetype=image/jpeg&rowid1=2';
```

mnemonic

Gets or sets the specified character(s) - typically an underlined letter- used with/without the modifier key(s) for the label, button or image.

Modifiers key values:

1 SHIFT

2 CTRL

4 Meta/CMD (Macintosh)

8 ALT(Windows, Unix); OPTION (Macintosh)

NOTE: A mnemonic is usually a single key used with/without the CTRL, CMD, SHIFT, ALT, or OPTION key(s) to activate a menu item or command - depending, in part on whether the mnemonic applies in a command line or graphic interface. For one description, you can refer to this web page: <http://msdn.microsoft.com/en-us/library/bb158536.aspx> or perform a search in a web browser search engine using the criteria "mnemonic".

NOTE2: Mnemonic is only supported in Smart Client.

Returns

[String](#)

Sample

```
//gets the mnemonic of the element
var my_mnemonic = forms.customer.elements.customer_id.mnemonic;

//sets the mnemonic of the element
forms.customer.elements.customer_id.mnemonic = 'f';
```

rolloverImageUrl

Gets/Sets the image displayed on a button or label roll over; based on URL.

Returns

[String](#)

Sample

```
//dynamically sets a roll over image displayed on a button or label
forms.customer.elements.customer_id.rolloverImageUrl = "http://www.servoy.com/images/test.gif";

//sets an image from your own image library
forms.customer.elements.customer_id.rolloverImageUrl = "media:///arrow.gif";

//loads an image (BLOB) from a field in a selected record into HTML
forms.customer.elements.customer_id.rolloverImageUrl = 'media:///servoy_blobloader?datasource='+controller.
getDataSource()+'&datapvider=image_data&mimetype=image/jpeg&rowid1=2';
```

toolTipText

Gets or sets the tool tip text of an element; text displays when the mouse cursor hovers over an element.

NOTE: HTML should be used for multi-line tooltips; you can also use any valid HTML tags to format tooltip text.

Returns

[String](#)

Sample

```
//gets the tooltip text of the element
var tooltip = forms.customer.elements.customer_id.tooltipText;

//sets the tooltip text of the element
forms.customer.elements.customer_id.tooltipText = "New tip";
forms.customer.elements.customer_id.tooltipText = "<html>This includes <b>bolded text</b> and <font
color='blue'>BLUE</font> text as well.";
```

transparent

Gets or sets the transparency of an element; true - transparent; false - not transparent.

NOTE: transparency can be inverted using ! operator: elements.elementName.transparent = !elements.elementName.transparent;

NOTE: transparency will be mostly used for background color, a transparent element will receive the background of the element "beneath" it, a non transparent one will use its own background color

Returns

[Boolean](#)

Sample

```
//gets the transparency of the element
var currentState = forms.customer.elements.customer_id.transparent;

//sets the transparency of the element
forms.customer.elements.customer_id.transparent = !currentState;
```

visible

Gets or sets the visibility of an element; true - visible; false - not visible; ! - the visibility state is inverted (the opposite).

NOTE: The visibility of an element is not persistent; the state of visibility only applies to the current user in his/her current session.

Returns

[Boolean](#)

Sample

```
//sets the element as visible
forms.company.elements.faxBtn.visible = true;

//gets the visibility of the element
var currentState = forms.company.elements.faxBtn.visible;

//sets the element as not visible when the current state is visible
forms.company.elements.faxBtn.visible = !currentState;
```

Method Details**getAbsoluteFormLocationY**

[Number](#) **getAbsoluteFormLocationY** ()

Returns the absolute form (designed) Y location.

Returns

[Number](#) - The y location of the form in pixels.

Sample

```
var absolute_y = forms.customer.elements.customer_id.getAbsoluteFormLocationY();
```

getClientProperty

[Object](#) **getClientProperty** (key)

Gets the specified client property for the element based on a key.

NOTE: Depending on the operating system, a user interface property name may be available.

Parameters

`{Object}` key - user interface key (depends on operating system)

Returns

`Object` - The value of the property for specified key.

Sample

```
var property = forms.customer.elements.customer_id.getClientProperty('ToolTipText');
```

getDataProviderID

`String` `getDataProviderID ()`

Get the data provider this UI element (display) is showing.

Returns

`String` - The data provider as String.

Sample

```
forms.customer.elements.customer_id.getDataProviderID();
```

getDesignTimeProperty

`Object` `getDesignTimeProperty ()`

Get a design-time property of an element.

Returns

`Object`

Sample

```
var prop = forms.orders.elements.mylabel.getDesignTimeProperty('myprop')
```

getElementType

`String` `getElementType ()`

Returns the type of a specified element.

Returns

`String` - The display type of the element as String.

Sample

```
var et = forms.customer.elements.customer_id.getElementType();
```

getHeight

`Number` `getHeight ()`

Returns the height of the current element.

NOTE: `getHeight()` can be used with `getWidth()` to set the size of an element using the `setSize` function. For example:

```
//returns the width (w) and height (h)
var w = forms.company.elements.faxBtn.getWidth();
var h = forms.company.elements.faxBtn.getHeight();

//sets the new size
forms.company.elements.faxBtn.setSize(w,h);

//sets the new size and adds 1 px to both the width and height
forms.company.elements.faxBtn.setSize(w+1,h+1);
```

Returns

`Number` - The height of the element in pixels.

Sample

```
var ht = forms.customer.elements.customer_id.getHeight();
```

getLabelForElementName

String `getLabelForElementName ()`

Gets the label for property of a label. This property is used to link a label to a certain element (by default used for tableview header, form security, can be used for custom purposes).

Returns

String - The label for property (String).

Sample

```
var name = forms.customer.elements.customer_id.getLabelForElementName();
```

getLocationX

Number `getLocationX ()`

Returns the x location of the current element.

NOTE: getLocationX() can be used with getLocationY() to set the location of an element using the setLocation function. For Example:

```
//returns the X and Y coordinates
var x = forms.company.elements.faxBtn.getLocationX();
var y = forms.company.elements.faxBtn.getLocationY();

//sets the new location 10 px to the right; 10 px down from the current location
forms.company.elements.faxBtn.setLocation(x+10,y+10);
```

Returns

Number - The x location of the element in pixels.

Sample

```
var x = forms.customer.elements.customer_id.getLocationX();
```

getLocationY

Number `getLocationY ()`

Returns the y location of the current element.

NOTE: getLocationY() can be used with getLocationX() to set the location of an element using the setLocation function. For Example:

```
//returns the X and Y coordinates
var x = forms.company.elements.faxBtn.getLocationX();
var y = forms.company.elements.faxBtn.getLocationY();

//sets the new location 10 px to the right; 10 px down from the current location
forms.company.elements.faxBtn.setLocation(x+10,y+10);
```

Returns

Number - The y location of the element in pixels.

Sample

```
var y = forms.customer.elements.customer_id.getLocationY();
```

getName

String `getName ()`

Returns the name of an element. (may be null as well)

Returns

String - The name of the element.

Sample

```
var name = forms.customer.elements.customer_id.getName();
```

getThumbnailJPGImage

byte[] `getThumbnailJPGImage ()`

Returns the image data in .jpg format from an icon; thumbnailing only works in record view.

Returns

byte[] - An array of bytes.

Sample

```
var jpgData = forms.customer.elements.customer_id.getThumbnailJPGImage();
plugins.file.writeFile("mypicture.jpg", jpgData);
```

getThumbnailJPGImage

byte[] **getThumbnailJPGImage** (width, height)

Returns the image data in .jpg format from an icon; thumbnailing only works in record view.

Parameters

{[Number](#)} width - The target width, use -1 for original image width.
 {[Number](#)} height - The target height, use -1 for original image height.

Returns

byte[] - An array of bytes.

Sample

```
var jpgData = forms.customer.elements.customer_id.getThumbnailJPGImage(50, 50);
plugins.file.writeFile("mypicture.jpg", jpgData);
```

getWidth

[Number](#) **getWidth** ()

Returns the width of the current element.

NOTE: getWidth() can be used with getHeight() to set the size of an element using the setSize function. For Example:

```
//returns the width (w) and height (h)
var w = forms.company.elements.faxBtn.getWidth();
var h = forms.company.elements.faxBtn.getHeight();

//sets the new size
forms.company.elements.faxBtn.setSize(w,h);

//sets the new size and adds 1 px to both the width and height
forms.company.elements.faxBtn.setSize(w+1,h+1);
```

Returns

[Number](#) - The width of the element in pixels.

Sample

```
var w = forms.customer.elements.customer_id.getWidth();
```

putClientProperty

void **putClientProperty** (key, value)

Sets the value for the specified element client property key.

NOTE: Depending on the operating system, a user interface property name may be available.

Parameters

{[Object](#)} key - user interface key (depends on operating system)
 {[Object](#)} value - a predefined value for the key

Returns

void

Sample

```
forms.customer.elements.customer_id.putClientProperty('ToolTipText','some text');
```

setLocation

void **setLocation** (x, y)

Sets the location of an element. It takes as input the X (horizontal) and Y (vertical) coordinates - starting from the TOP LEFT side of the screen. Please note that location should not be altered at runtime when an element is anchored. Use the solutionModel in such a situation.

NOTE: getLocationX() can be used with getLocationY() to return the current location of an element; then use the X and Y coordinates with the setLocation function to set a new location. For Example:

```
//returns the X and Y coordinates
var x = forms.company.elements.faxBtn.getLocationX();
var y = forms.company.elements.faxBtn.getLocationY();

//sets the new location 10 px to the right; 10 px down from the current location
forms.company.elements.faxBtn.setLocation(x+10,y+10);
```

Parameters

{Number} x - the X coordinate of the element in pixels.
{Number} y - the Y coordinate of the element in pixels.

Returns

void

Sample

```
forms.customer.elements.customer_id.setLocation(200,200);
```

setSize

void **setSize** (width, height)

Sets the size of an element. It takes as input the width and the height. Please note that size should not be altered at runtime when an element is anchored. Use the solutionModel in such a situation.

NOTE: getWidth() can be used with getHeight() to set the size of an element using the setSize function. For Example:

```
//returns the width (w) and height (h)
var w = forms.company.elements.faxBtn.getWidth();
var h = forms.company.elements.faxBtn.getHeight();

//sets the new size
forms.company.elements.faxBtn.setSize(w,h);

//sets the new size and adds 1 px to both the width and height
forms.company.elements.faxBtn.setSize(w+1,h+1);
```

Parameters

{Number} width - the width of the element in pixels.
{Number} height - the height of the element in pixels.

Returns

void

Sample

```
forms.customer.elements.customer_id.setSize(20,30);
```