

Part

Property Summary

Boolean	allowBreakAcrossPageBounds When set, the remainder of a selected part that does not fit on the page currently being printed, will not be transported to the next page - it will break where the page ends and continue on the next page.
String	background The background color of the form part.
Boolean	discardRemainderAfterBreak When set, the remainder of a selected part that is broken due to the page ending will not be printed on the next page - it will be discarded.
String	groupbyDataProviderIDs For Leading Subsummary or Trailing Subsummary parts, one or more dataproviders can be added as Break (GroupBy) dataproviders.
Number	height The height of a selected part; specified in pixels.
Number	pageBreakAfterOccurrence A page break will be inserted after a specified number of occurrences of a selected part.
Boolean	pageBreakBefore When set, a page break will be inserted before each occurrence of a selected part.
Number	partType The type of this part.
Boolean	restartPageNumber When set, page numbering will be restarted after each occurrence of a selected part.
Boolean	sinkWhenLast When set, the last part on a page (such as a Trailing Grand Summary part) will "sink" to the lowest part of the page when there is free space.
String	styleClass The Cascading Style Sheet (CSS) class name applied to the part.

Property Details

allowBreakAcrossPageBounds

When set, the remainder of a selected part that does not fit on the page currently being printed, will not be transported to the next page - it will break where the page ends and continue on the next page.

NOTE: Make sure to set this option when you are printing more than one page per record.

Returns

[Boolean](#)

background

The background color of the form part.

NOTE: When no background color has been set, the default background color will be determined by the Look and Feel (LAF) that has been selected in Application Preferences.

Returns

[String](#)

discardRemainderAfterBreak

When set, the remainder of a selected part that is broken due to the page ending will not be printed on the next page - it will be discarded.

Returns

[Boolean](#)

groupbyDataProviderIDs

For Leading Subsummary or Trailing Subsummary parts, one or more dataproviders can be added as Break (GroupBy) dataproviders. The Leading/Trailing Subsummary parts will be displayed once for each resulted group of data.

Returns

[String](#)

height

The height of a selected part; specified in pixels.

This height property is the lowerbound as its ending Y value (0 == top of the form).

Returns

Number

pageBreakAfterOccurrence

A page break will be inserted after a specified number of occurrences of a selected part.

Returns

Number

pageBreakBefore

When set, a page break will be inserted before each occurrence of a selected part.

Returns

Boolean

partType

The type of this part.

Returns

Number

restartPageNumber

When set, page numbering will be restarted after each occurrence of a selected part.

Returns

Boolean

sinkWhenLast

When set, the last part on a page (such as a Trailing Grand Summary part) will "sink" to the lowest part of the page when there is free space.

Returns

Boolean

styleClass

The Cascading Style Sheet (CSS) class name applied to the part.

Returns

String