

JSTableObject

Method Summary

JSColumnObject	createNewColumn (columnName, type, length)	Creates a new column in this table.
JSColumnObject	createNewColumn (columnName, type, length, allowNull)	Creates a new column in this table.
JSColumnObject	createNewColumn (columnName, type, length, allowNull, pkColumn)	Creates a new column in this table.
void	deleteColumn (columnName)	Deletes the column with the specified name from this table.
JSColumn	getColumn (name)	Returns a JSColumn for the named column (or column dataproviderID).
String[]	getColumnNames ()	Returns an array containing the names of all table columns.
String	getDataSource ()	Returns the table data source uri.
String	getQuotedSQLName ()	Returns a quoted version of the table name, if necessary, as defined by the actual database used.
String[]	getRowIdentifierColumnNames ()	Returns an array containing the names of the identifier (PK) column(s).
String	getSQLName ()	Returns the table name.
String	getServerName ()	Returns the Servoy server name.
Boolean	isMetadataTable ()	Returns whether table was flagged as metadata table.

Method Details

createNewColumn

JSColumnObject [createNewColumn](#) (columnName, type, length)

Creates a new column in this table. The name, type and length of the new column must be specified. For specifying the type of the column, use the JSColumn constants. The column is not actually created in the database until this table is synchronized with the database using the JSServer.synchronizeWithDB method.

The method returns a JSColumn instance that corresponds to the newly created column. If any error occurs and the column cannot be created, then the method returns null.

Parameters

[String](#) columnName
[Number](#) type
[Number](#) length

Returns

[JSColumnObject](#)

Sample

```

var server = plugins.maintenance.getServer("example_data");
if (server)
{
    var table = server.createNewTable("users");
    if (table)
    {
        var pk = table.createNewColumn("id", JSColumn.MEDIA, 16); // can also use (JSColumn.TEXT,
36) for UUIDs
        pk.rowIdentifierType = JSColumn.PK_COLUMN;
        pk.setFlag(JSColumn.UUID_COLUMN, true)
        pk.sequenceType = JSColumn.UUID_GENERATOR
        var c = table.createNewColumn("name", JSColumn.TEXT, 100);
        c.allowNull = false
        table.createNewColumn("age", JSColumn.INTEGER, 0);
        table.createNewColumn("last_login", JSColumn.DATETIME, 0);
        var result = server.synchronizeWithDB(table);
        if (result) application.output("Table successfully created.");
        else application.output("Table not created.");
    }
}

```

createNewColumn

JSColumnObject **createNewColumn** (columnName, type, length, allowNull)

Creates a new column in this table. The name, type and length of the new column must be specified. For specifying the type of the column, use the JSColumn constants. The column is not actually created in the database until this table is synchronized with the database using the JSServer.synchronizeWithDB method.

The method returns a JSColumn instance that corresponds to the newly created column. If any error occurs and the column cannot be created, then the method returns null.

Parameters

{String} columnName
 {Number} type
 {Number} length
 {Boolean} allowNull

Returns

JSColumnObject

Sample

```

var server = plugins.maintenance.getServer("example_data");
if (server)
{
    var table = server.createNewTable("users");
    if (table)
    {
        var pk = table.createNewColumn("id", JSColumn.MEDIA, 16); // can also use (JSColumn.TEXT,
36) for UUIDs
        pk.rowIdentifierType = JSColumn.PK_COLUMN;
        pk.setFlag(JSColumn.UUID_COLUMN, true)
        pk.sequenceType = JSColumn.UUID_GENERATOR
        var c = table.createNewColumn("name", JSColumn.TEXT, 100);
        c.allowNull = false
        table.createNewColumn("age", JSColumn.INTEGER, 0);
        table.createNewColumn("last_login", JSColumn.DATETIME, 0);
        var result = server.synchronizeWithDB(table);
        if (result) application.output("Table successfully created.");
        else application.output("Table not created.");
    }
}

```

createNewColumn

JSColumnObject **createNewColumn** (columnName, type, length, allowNull, pkColumn)

Creates a new column in this table. The name, type and length of the new column must be specified. For specifying the type of the column, use the JSColumn constants. The column is not actually created in the database until this table is synchronized with the database using the JSServer.synchronizeWithDB method.

The method returns a JSColumn instance that corresponds to the newly created column. If any error occurs and the column cannot be created, then the method returns null.

Parameters

{String} columnName
 {Number} type
 {Number} length
 {Boolean} allowNull
 {Boolean} pkColumn

Returns

JSColumnObject

Sample

```
var server = plugins.maintenance.getServer("example_data");
if (server)
{
    var table = server.createNewTable("users");
    if (table)
    {
        var pk = table.createNewColumn("id", JSColumn.MEDIA, 16); // can also use (JSColumn.TEXT,
36) for UUIDs
        pk.rowIdentifierType = JSColumn.PK_COLUMN;
        pk.setFlag(JSColumn.UUID_COLUMN, true)
        pk.sequenceType = JSColumn.UUID_GENERATOR
        var c = table.createNewColumn("name", JSColumn.TEXT, 100);
        c.allowNull = false
        table.createNewColumn("age", JSColumn.INTEGER, 0);
        table.createNewColumn("last_login", JSColumn.DATETIME, 0);
        var result = server.synchronizeWithDB(table);
        if (result) application.output("Table successfully created.");
        else application.output("Table not created.");
    }
}
```

deleteColumn

void **deleteColumn** (columnName)

Deletes the column with the specified name from this table. The column is not actually deleted from the database until this table is synchronized with the database using the JSServer.synchronizeWithDB method.

Parameters

{String} columnName

Returns

void

Sample

```
var server = plugins.maintenance.getServer("example_data");
if (server) {
    var table = server.getTable("users");
    if (table) {
        table.deleteColumn("last_login");
        server.synchronizeWithDB(table);
    }
}
```

getColumn

JSColumn **getColumn** (name)

Returns a JSColumn for the named column (or column dataproviderID).

Parameters

{String} name - The name of the column to return the value from.

Returns

JSColumn - JSColumn column.

Sample

```
var jsTable = databaseManager.getTable('udm', 'campaigns')
var jsColumn = jsTable.getColumn('campaign_name')
```

getColumnNames

String[] `getColumnNames ()`

Returns an array containing the names of all table columns.

Returns

String[] - String array of column names.

Sample

```
var jsTable = databaseManager.getTable('udm', 'campaigns')
var columnNames = jsTable.getColumnNames()
```

getDataSource

String `getDataSource ()`

Returns the table data source uri.

Returns

String - String datasource uri.

Sample

```
var jsTable = databaseManager.getTable('udm', 'campaigns')
var dataSource = jsTable.getDataSource()
```

getQuotedSQLName

String `getQuotedSQLName ()`

Returns a quoted version of the table name, if necessary, as defined by the actual database used.

Returns

String - String table name, quoted if needed.

Sample

```
//use with the raw SQL plugin:
//if the table name contains characters that are illegal in sql, the table name will be quoted
var jsTable = databaseManager.getTable('udm', 'campaigns')
var quotedTableName = jsTable.getQuotedSQLName()
plugins.rawSQL.executeSQL('udm', quotedTableName, 'select * from ' + quotedTableName + ' where is_active = ?', [1])
```

getRowIdentifierColumnNames

String[] `getRowIdentifierColumnNames ()`

Returns an array containing the names of the identifier (PK) column(s).

Returns

String[] - String array of row identifier column names.

Sample

```
var jsTable = databaseManager.getTable('udm', 'campaigns')
var identifierColumnNames = jsTable.getRowIdentifierColumnNames()
```

getSQLName

String `getSQLName ()`

Returns the table name.

Returns

String - String table name.

Sample

```
var jsTable = databaseManager.getTable('udm', 'campaigns')
var tableNameForDisplay = jsTable.getSQLName()
```

getServerName

String `getServerName ()`

Returns the Servoy server name.

Returns

String - String server name.

Sample

```
var jsTable = databaseManager.getTable('udm', 'campaigns')
var serverName = jsTable.getServerName()
```

isMetadataTable

Boolean `isMetadataTable ()`

Returns whether table was flagged as metadata table.

Returns

Boolean - boolean is metadata

Sample

```
var jsTable = databaseManager.getTable('udm', 'campaigns')
var isMetadataTable = jsTable.isMetadataTable()
```