

# JSAuthenticateRequest

## Method Summary

```
void      addAttributeRequest(alias, schemaURI, required)
Add attribute request
void      execute()
```

## Method Details

### **addAttributeRequest**

```
void addAttributeRequest (alias, schemaURI, required)
    Add attribute request
```

#### Parameters

```
{String} alias
{String} schemaURI
{Boolean} required
```

#### Returns

```
void
```

#### Sample

```
authenticateRequest.addAttributeRequest('email','http://axschema.org/contact/email',true);
```

### **execute**

```
void execute ()
```

#### Returns

```
void
```

#### Sample

```
var authenticateRequest = plugins.openid.createAuthenticateRequest('https://www.google.com/accounts/o8/id',
openIDLoginCallback);
authenticateRequest.addAttributeRequest('email','http://axschema.org/contact/email',true);
//see http://www.axschema.org/types/ for more attributes, not all are supported by all providers!
authenticateRequest.execute();

//sample
//function openIDLoginCallback(identifier,authenticateResult)
//{
//    var ok = false;
//    if (identifier)
//    {
//        var id = identifier.substring(identifier.lastIndexOf('=')+1)
//        application.output('id:' + id)
//        var email = authenticateResult.getAttributeValue('email')
//        application.output('email:' + email)
//        ok = security.login(email, id, ['Administrators'])
//    }
//    if (!ok)
//    {
//        application.output('Login failed')
//    }
//}
```