

# Table

Event Summary	
	<a href="#">onAfterCreate</a> A method that is executed after a new record is created.
	<a href="#">onAfterDelete</a> A method that is executed after a delete operation.
	<a href="#">onAfterFind</a> A method that is executed after a foundset has switched to find mode.
	<a href="#">onAfterInsert</a> A method that is executed after an insert operation.
	<a href="#">onAfterSearch</a> A method that is executed after a search is executed for a foundset.
	<a href="#">onAfterUpdate</a> A method that is executed after an update operation.
Boolean	<a href="#">onCreate</a> A method that is executed before a record is created.
Boolean	<a href="#">onDelete</a> A method that is executed before a delete operation.
Boolean	<a href="#">onFind</a> A method that is executed before a foundset is going into find mode.
Boolean	<a href="#">onInsert</a> A method that is executed before an insert operation.
Boolean	<a href="#">onSearch</a> A method that is executed before search() is called on a foundset in find mode.
Boolean	<a href="#">onUpdate</a> A method that is executed before an update operation.

Event Details	
<b>onAfterCreate</b> A method that is executed after a new record is created.	
<b>Parameters</b>  <code>{JSRecord}</code> record - record that is created	
<b>onAfterDelete</b> A method that is executed after a delete operation.	
<b>Parameters</b>  <code>{JSRecord}</code> record - record that is deleted	
<b>onAfterFind</b> A method that is executed after a foundset has switched to find mode.	
<b>onAfterInsert</b> A method that is executed after an insert operation.	
<b>Parameters</b>  <code>{JSRecord}</code> record - record that is inserted	
<b>onAfterSearch</b> A method that is executed after a search is executed for a foundset.	
<b>onAfterUpdate</b> A method that is executed after an update operation.	
<b>Parameters</b>  <code>{JSRecord}</code> record - record that is updated	
<b>onCreate</b> A method that is executed before a record is created. The method can block the creation by returning false.	
<b>Returns</b>  <code>Boolean</code>	

**onDelete**

A method that is executed before a delete operation. The method can block the delete operation by returning false.

**Parameters**

{JSRecord} record - record that will be deleted

**Returns**

Boolean

**onFind**

A method that is executed before a foundset is going into find mode. The method can block the mode change.

**Returns**

Boolean

**onInsert**

A method that is executed before an insert operation. The method can block the insert operation by returning false.

**Parameters**

{JSRecord} record - record that will be inserted

**Returns**

Boolean

**onSearch**

A method that is executed before search() is called on a foundset in find mode. The method can block the search (foundset will stay in find mode).

**Parameters**

{Boolean} clearLastResults

{Boolean} reduceSearch

**Returns**

Boolean

**onUpdate**

A method that is executed before an update operation. A method can block the update by returning false.

**Parameters**

{JSRecord} record - record that will be updated

**Returns**

Boolean