

openid

Return Types

[JSAuthenticateRequest](#) [JSAuthenticateResult](#)

Method Summary

[JSAuthenticateRequest](#) [createAuthenticateRequest](#)([identifier](#), [callback](#))
[request](#) Redirect to openID provider to login, callback method will receive answer.

Method Details

createAuthenticateRequest

[JSAuthenticateRequest](#) [createAuthenticateRequest](#) ([identifier](#), [callback](#))
Redirect to openID provider to login, callback method will receive answer.

Parameters

[String](#) [identifier](#)
[Function](#) [callback](#)

Returns

[JSAuthenticateRequest](#)

Sample

```
var authenticateRequest = plugins.openid.createAuthenticateRequest('https://www.google.com/accounts/o8/id',
openidLoginCallback);
authenticateRequest.addAttributeRequest('email', 'http://axschema.org/contact/email', true);
//see http://www.axschema.org/types/ for more attributes, not all are supported by all providers!
authenticateRequest.execute();

//sample
//function openidLoginCallback(identifier, authenticateResult)
//{
//    var ok = false;
//    if (identifier)
//    {
//        var id = identifier.substring(identifier.lastIndexOf('=')+1);
//        application.output('id:'+id);
//        var email = authenticateResult.getAttributeValue('email');
//        application.output('email:'+email);
//        ok = security.login(email, id, ['Administrators']);
//    }
//    if (!ok)
//    {
//        application.output('Login failed')
//    }
//}
```