

QBLogicalCondition

Property Summary

[QBTableClause](#) [parent](#)
Get query builder parent table clause, this may be a query or a join clause.

[QBSelect](#) [root](#)
Get query builder parent.

Method Summary

[QBLogicalCondition](#) [add](#)(condition)
[on](#) Add a condition to the AND or OR condition list.

Property Details

parent

Get query builder parent table clause, this may be a query or a join clause.

Returns

[QBTableClause](#)

Sample

```
/** @type {QBSelect<db:/example_data/person>} */
var query = databaseManager.createSelect('db:/example_data/person')
query.where.add(query.joins.person_to_parent.joins.person_to_parent.columns.name.eq('john'))
foundset.loadRecords(query)
```

root

Get query builder parent.

Returns

[QBSelect](#)

Sample

```
/** @type {QBSelect<db:/example_data/order_details>} */
var subquery = databaseManager.createSelect('db:/example_data/order_details')

/** @type {QBSelect<db:/example_data/orders>} */
var query = databaseManager.createSelect('db:/example_data/orders')
query.where.add(query
    .or
        .add(query.columns.order_id.not.isIn([1, 2, 3]))
        .add(query.exists(
            subquery.where.add(subquery.columns.orderid.eq(query.columns.
order_id)).root
        ))
    )
foundset.loadRecords(query)
```

Method Details

add

[QBLogicalCondition](#) **add** (condition)

Add a condition to the AND or OR condition list.

Parameters

{[QBCondition](#)} condition - the condition to add

Returns

[QBLogicalCondition](#)

Sample

```
/** @type {QBSelect<db:/example_data/orders>} */  
var query = databaseManager.createSelect('db:/example_data/orders')  
query.where.add(query.columns.orderdate.isNull)
```