

Response

Method Summary

String	getCharset() Get the charset of the response body.
byte[]	getMediaData() Get the content of response as binary data.
String	getResponseBody() Get the content of the response as String.
Object	getResponseHeaders() Gets the headers of the response as name/value arrays.
Object	getResponseHeaders(headerName) Gets the headers of the response as name/value arrays.
Number	getStatusCode() Gets the status code of the response, the list of the possible values is in HTTP_STATUS constants.

Method Details

getCharset

[String](#) [getCharset\(\)](#)

Get the charset of the response body.

Returns

[String](#)

Sample

```
var charset = response.getCharset();
```

getMediaData

[byte\[\]](#) [getMediaData\(\)](#)

Get the content of response as binary data. It also supports gzip-ed content.

Returns

[byte\[\]](#)

Sample

```
var mediaData = response.getMediaData();
```

getResponseBody

[String](#) [getResponseBody\(\)](#)

Get the content of the response as String.

Returns

[String](#)

Sample

```
var pageData = response.getResponseBody();
```

getResponseHeaders

[Object](#) [getResponseHeaders\(\)](#)

Gets the headers of the response as name/value arrays.

Returns

[Object](#)

Sample

```
var allHeaders = response.getResponseHeaders();
var header;

for (header in allHeaders) application.output(header + ': ' + allHeaders[header]);
```

getResponseHeaders

Object **getResponseHeaders** (headerName)

Gets the headers of the response as name/value arrays.

Parameters

{**String**} headerName

Returns

Object

Sample

```
var contentLength = response.getResponseHeaders("Content-Length");
```

getStatusCode

Number **getStatusCode** ()

Gets the status code of the response, the list of the possible values is in HTTP_STATUS constants.

Returns

Number

Sample

```
var status = response.getStatusCode();// compare with HTTP_STATUS constants
```