

# Solution

## Event Summary

Boolean	<a href="#">onClose</a> The method that is executed when a solution closes.
	<a href="#">onDataBroadcast</a> Method that is executed when data broadcast occurs.
Boolean	<a href="#">onError</a> The method that is executed when a solution opens and an error occurs.
	<a href="#">onOpen</a> The method that is executed when a solution opens.

## Property Summary

Number	<a href="#">firstForm</a> The first form that loads when a solution is deployed.
String	<a href="#">i18nDataSource</a> The i18n database server connection and database table that stores the i18n keys for a solution.
Number	<a href="#">loginForm</a> The name of the login form that loads when a solution is deployed.
String	<a href="#">loginSolutionName</a> Get the first module that is also a login solution.
String	<a href="#">modulesNames</a> The list of modules that have been added to a solution.
Boolean	<a href="#">mustAuthenticate</a> Flag that tells if authentication is needed in order to access the solution.
Number	<a href="#">solutionType</a> The type of a solution; can be "Normal" (non-module), "Module", "Web client only", "Smart client only", "Login", "Authenticator", "Pre-import hook module", "Post-import hook module", "Mobile".
Number	<a href="#">textOrientation</a> The direction that text is displayed.
String	<a href="#">titleText</a> The menu bar title of a solution.

## Event Details

### onClose

The method that is executed when a solution closes. The default is -none-.

#### Parameters

{[Boolean](#)} force - if false then solution close can be stopped by returning false

#### Returns

[Boolean](#)

### onDataBroadcast

Method that is executed when data broadcast occurs. The default is -none-.

#### Parameters

{[String](#)} dataSource - table data source  
 {[Number](#)} action - see SQL\_ACTION\_TYPES constants  
 {[JSDataSet](#)} pks - affected primary keys  
 {[Boolean](#)} cached - data was cached

### onError

The method that is executed when a solution opens and an error occurs. The default is -none-.

#### Parameters

ex - exception to handle

#### Returns

[Boolean](#)

### onOpen

---

The method that is executed when a solution opens. The default is -none-.

## Property Details

### firstForm

The first form that loads when a solution is deployed.

NOTE: If the Login form is specified, then the firstForm is the first form that will load next after the loginForm.

#### Returns

Number

### i18nDataSource

The i18n database server connection and database table that stores the i18n keys for a solution.

#### Returns

String

### loginForm

The name of the login form that loads when a solution is deployed.

#### Returns

Number

### loginSolutionName

Get the first module that is also a login solution.

#### Returns

String

### modulesNames

The list of modules that have been added to a solution.

#### Returns

String

### mustAuthenticate

Flag that tells if authentication is needed in order to access the solution.

To enforce a default Servoy user name and password login dialog; if set a login dialog is required, if unchecked no login dialog is required.

#### Returns

Boolean

### solutionType

The type of a solution; can be "Normal" (non-module), "Module", "Web client only", "Smart client only", "Login", "Authenticator", "Pre-import hook module", "Post-import hook module", "Mobile".  
These constants are defined in SolutionMetaData class.

#### Returns

Number

### textOrientation

The direction that text is displayed.

Options include:  
DEFAULT  
left to right  
right to left  
locale specific

#### Returns

Number

### titleText

The menu bar title of a solution.

#### Returns

String

